

## preLink M12 housing empty



Image is for illustration purposes only. Please refer to product description.

Part number	20 82 000 1210
Specification	preLink M12 housing empty
HARTING eCatalogue	<a href="https://harting.com/20820001210">https://harting.com/20820001210</a>

### Identification

Category	Connectors
Series	preLink® Circular connectors M12
Element	Empty housing
Type of hood/housing	Screw mounted housing

### Version

Gender	Male
Locking type	Screw locking

### Technical characteristics

Limiting temperature	-40 ... +85 °C
Degree of protection acc. to IEC 60529	IP65 IP67
Cable diameter	5 ... 9.5 mm
Vibration resistance	5.72 m/s <sup>2</sup> acc. to IEC 61373 Category 1 Class B
Shock resistance	5 g / 30 ms, 5 shocks / axis and direction acc. to IEC 61373 Category 1 Class B

### Material properties

Material (hood/housing)	Zinc die-cast
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

REACH ANNEX XIV substances Not contained

REACH SVHC substances Not contained

## Specifications and approvals

Specifications EN 45545-2

UL / CSA UL 1863 DUXR2.E470046  
CSA-C22.2 No. 182.4, No. 233-09 DUXR8.E470046

Approvals DNV GL

PROFINET Yes

## Commercial data

Packaging size 1

Net weight 25 g

Country of origin Latvia

European customs tariff number 85389099

GTIN 5713140135499

eCl@ss 27440224 Shell for circular connectors

ETIM EC003556

UNSPSC 24.0 39121405