

Keystone Patch panel, loaded



Image is for illustration purposes only. Please refer to product description.

Part number	20 82 405 0001
Specification	Keystone Patch panel, loaded
HARTING eCatalogue	https://harting.com/20824050001

Identification

Category	Connectors
Series	preLink®
Element	Patch panel

Version

Size	Keystone version
Fixing	In 19" racks acc. to IEC/DIN EN 60 297-3-100 (DIN 41 494-1)
Details	This item requires additional a termination block. Please select these under "Matching Products".
Pack contents	24 preLink® RJ45 keystone jack 24 terminal modules for AWG 22 / 23 24 cable ties

Technical characteristics

Conductor cross-section	0.22 ... 0.32 mm ²
Conductor cross-section [AWG]	AWG 24 ... AWG 22
Transmission characteristics	Cat. 6 Class E _A up to 500 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s
Limiting temperature	-40 ... +85 °C
Degree of protection acc. to IEC 60529	IP20
Vibration resistance	5.72 m/s ² acc. to IEC 61373 Category 1 Class B



Pushing Performance
Since 1945

Technical characteristics

Shock resistance 5 g / 30 ms, 5 shocks / axis and direction acc. to IEC 61373 Category 1 Class B

Material properties

Material (insert)	Steel sheet
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

Specifications and approvals

Specifications	EN 45545-2
Approvals	DNV GL
PROFINET	Yes

Commercial data

Packaging size	1
Net weight	1,607.2 g
Country of origin	Czechia
European customs tariff number	85389099
GTIN	5713140135727
ETIM	EC002943
eCl@ss	27440292 Connector component (accessories)