


**RESEDA LED power supply unit 12 V DC for 3900.. / 3901.., switchable**

Article no. 3559


**Tender**

LED power supply unit 12 V DC for 3900.. / 3901.. switchable, Round. Ceiling cut-out Installation depth mm, Outer diameter 57,5 mm, Weight 0,052 kg, with max: 10 W , Delivery without bulb.Housing material: Plastic, Colour: white, Permissible ambient temperature (ta): 0 °C up to +40 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20. For connection to an external driver, which is not included in the scope of delivery of the luminaire. on/off switchable.

Article data	
Article no.	3559
GTIN	4250047751137
Series name	RESEDA
Short description	LED power supply unit 12 V DC for 3900.. / 3901.., switchable
Material	Plastic
Colour	white
Shape	Round
Outer diameter	57.5 mm
Hight	19 mm
Weight	0.052 kg
Conformance	CE, UKCA


**RESEDA LED power supply unit 12 V DC for 3900.. / 3901.., switchable**

Article no. 3559

Operating technology of driver	
AC nominal voltage max	230 V
Frequency min	47 Hz
Frequency max	63 Hz
Protection class	II
Degree of protection	IP20
Power	0.1 W
Power max.	10 W
Output voltage max	12.00 V
Control	on/off
Environment temperature (ta)	0 °C up to +40 °C
Measure point (tc)	max. +70 °C

Packing data	
Gross weight	0.062 kg
Length of packaging	85 mm
Packaging width	42 mm
Packaging height	84 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>