






## QUALITYFLEX COB-Vision HE LED flex board, 5 m, CRI > 90, 15 W / m, IP67

Article no. 15577027



### Tender

LED flex board, 5 m, CRI > 90, 15 W / m, IP67, white, Light colour: white, 2.700K, CRI > 90. Length: 5000 mm . Lamp power per meter: 15.0 W/m, Luminous flux per meter: 1935.0 lm/m, Degree of protection: IP67, Protection class: III, Voltage: 24V DC, Beam angle: 120.0 °, 288 LEDs per meter, Chip distance (Short Pitch) : 3,47mm. For individual application, the LED flex board can be used all 27,77 mm be cut back. If the LED flex board is shortened, the IP protection must be restored by the customer. The maximum system length of 5.000 mm must not be exceeded with one feed-in.

### Product Benefits

- Divisible every 27.77 mm.
- Suitable for indoor (IP00) and outdoor (IP67) applications.
- Up to 144 lm per watt.
- Flexible mounting in profiles due to small pitch.
- Length 5,000 mm with a pitch of 27.77 mm.
- Available in 2,700 K, 3,000 K and 4,000 K.
- Dimmable with corresponding accessories.


**QUALITYFLEX COB-Vision HE LED flex board, 5 m, CRI > 90, 15 W / m, IP67**

Article no. 15577027

| Article data                  |   |
|-------------------------------|---|
| Article no.                   | 15577027  |
| GTIN                          | 4255752525639   |
| Series name                   | QUALITYFLEX COB-Vision HE   |
| Short description             | LED flex board, 5 m, CRI > 90, 15 W / m, IP67   |
| Colour                        | white   |
| Length                        | 5,000 mm  |
| Width                         | 12 mm   |
| Height                        | 5 mm  |
| Scope of delivery             | incl. 1 x assembly instruction, 5 x identification labels, 5 x silicone end caps, 10 x fixing clamps and 20 x countersunk screws. |
| Weight                        | 0.39 kg   |
| Length of the connection line | 300 mm  |
| Conformance                   | CE, UKCA  |

| Lighting technology          |               |
|------------------------------|---------------|
| Colour temperature           | 2.700 K       |
| Light colour                 | white         |
| Luminous flux per meter      | 1,935 lm/m    |
| System efficiency            | 129 lm/W      |
| McAdam-Step                  | McAdam-Step 5 |
| Colour rendering             | CRI > 90      |
| Beam angle                   | 120°          |
| Adjustable color temperature | No            |

| Operating technology of the luminaire |                                |
|---------------------------------------|--------------------------------|
| Lamp power per meter                  | 15 W/m                         |
| Voltage type                          | DC                             |
| DC nominal voltage max                | 24 V                           |
| Lamp                                  | LED                            |
| Protection class                      | III                            |
| Degree of protection                  | IP67                           |
| Ambient temperature                   | -10°C up to +40°C              |
| Dimmable                              | Yes                            |
| Wire number                           | 2                              |
| Control                               | Depending on driver            |
| Length of the connection line         | 300 mm                         |
| Cable assignment                      | rot = + pol<br>schwarz = - pol |
| Design of the connecting cable        | on both sides                  |
| Bulb change possible                  | No                             |
| Rated life time L70/B50 at 25 °C      | 161,900 h                      |
| Rated life time L80/B10 at 25 °C      | 75.500 h                       |
| Rated life time L80/B20 at 25 °C      | 81.200 h                       |

| Operating technology of QualityFlex |                     |
|-------------------------------------|---------------------|
| Power per meter                     | 15 W/m              |
| Short Pitch                         | 3.47 mm             |
| Number of lamps per meter           | 288 Qty             |
| Length of individual sections       | 27.77 mm            |
| Smallest bend radius                | 50 mm               |
| Length                              | 5,000 mm            |
| Maximum module length               | 5,000 mm            |
| Circuit type                        | Parallel conduction |
| LED Type                            | COB-LED             |


**QUALITYFLEX COB-Vision HE LED flex board, 5 m, CRI > 90, 15 W / m, IP67**

Article no. 15577027

| Packing data            |   |
|-------------------------|---|
| Gross weight            | 0.473 kg  |
| Length of packaging     | 255 mm  |
| Packaging width         | 275 mm  |
| Packaging height        | 20 mm   |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.<br>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |

| Compatible Driver |       |       |                     |          |         |        |
|-------------------|-------|-------|---------------------|----------|---------|--------|
| Article no.       |       | Power | Control             | Length   | Width   | Height |
| 17206000          | 1 W   | 20 W  | 1-10 V              | 146 mm   | 55 mm   | 19 mm  |
| 17207000          | 1 W   | 30 W  | on/off              | 160 mm   | 50 mm   | 22 mm  |
| 17214000          | 1 W   | 7.2 W | on/off              | 68 mm    | 35 mm   | 21 mm  |
| 17223000          | 1 W   | 75 W  | on/off              | 185 mm   | 60 mm   | 31 mm  |
| 17224000          | 1 W   | 100 W | on/off              | 199 mm   | 63 mm   | 36 mm  |
| 17225000          | 1 W   | 150 W | on/off              | 219 mm   | 63 mm   | 36 mm  |
| 17226000          | 1 W   | 240 W | on/off              | 244 mm   | 71 mm   | 38 mm  |
| 17227000          | 1 W   | 320 W | on/off              | 252 mm   | 90 mm   | 44 mm  |
| 17228000          | 1 W   | 480 W | on/off              | 262 mm   | 125 mm  | 44 mm  |
| 17230000          | 5 W   | 30 W  | Trailing-edge phase | 145 mm   | 50 mm   | 22 mm  |
| 17231000          | 12 W  | 75 W  | Trailing-edge phase | 185 mm   | 60 mm   | 31 mm  |
| 17232000          | 12 W  | 120 W | Trailing-edge phase | 223 mm   | 64 mm   | 32 mm  |
| 17340000          | 1.5 W | 30 W  | on/off              | 135 mm   | 36 mm   | 25 mm  |
| 17341000          | 3 W   | 60 W  | on/off              | 151.5 mm | 40.2 mm | 31 mm  |
| 17342000          | 6 W   | 120 W | on/off              | 253.2 mm | 42.5 mm | 31 mm  |
| 17343000          | 7.5 W | 150 W | on/off              | 253.2 mm | 42.5 mm | 31 mm  |
| 17250000          | 1 W   | 45 W  | DALI-2              | 187 mm   | 45 mm   | 31 mm  |
| 17251000          | 1 W   | 80 W  | DALI-2              | 290 mm   | 45 mm   | 31 mm  |
| 17252000          | 1 W   | 150 W | DALI-2              | 290 mm   | 45 mm   | 31 mm  |
| 17260000          | 1 W   | 150 W | on/off              | 105 mm   | 90 mm   | 59 mm  |

| Compatible Controller |       |       |                             |        |         |        |
|-----------------------|-------|-------|-----------------------------|--------|---------|--------|
| Article no.           |       | Power | Control                     | Length | Width   | Height |
| 17502000              | 1 W   | 120 W | DALI                        | 183 mm | 33 mm   | 23 mm  |
| 18151000              | 1 W   | 240 W | KNX                         | 170 mm | 59 mm   | 30 mm  |
| 18152000              | 1 W   | 240 W | DALI-DT6                    | 170 mm | 59 mm   | 30 mm  |
| 18153000              | 1 W   | 240 W | DMX                         | 170 mm | 59 mm   | 30 mm  |
| 18154000              | 1 W   | 240 W | 1-10 V                      | 170 mm | 59 mm   | 30 mm  |
| 18161000              | 1 W   | 240 W | KNX                         | 72 mm  | 90 mm   | 70 mm  |
| 18162000              | 1 W   | 240 W | DALI-DT6                    | 54 mm  | 110 mm  | 66 mm  |
| 18164000              | 1 W   | 240 W | 1-10 V                      | 54 mm  | 110 mm  | 66 mm  |
| 17528000              | 120 W | 240 W | Wireless technology control |        |         |        |
| 17511000              | 120 W | 240 W | Wireless technology control |        | 46.5 mm | 145 mm |
| 18157000              | 1 W   | 240 W | ZigBee                      | 145 mm | 46.5 mm | 16 mm  |
| 18192000              | 1 W   | 240 W | Wireless technology control | 160 mm | 45 mm   | 18 mm  |



**QUALITYFLEX COB-Vision HE LED flex board, 5 m, CRI > 90, 15 W / m, IP67**  
Article no. 15577027

| Compatible Profiles                       |  |  |  |  |
|---|--|--|--|--|
| Short description                         |  |  |  |  |
| Recessed profile<br>53654070              |  |  |  |  |
| LED recessed profile<br>53759070          |  |  |  |  |
| Plaster profile<br>53655070               |  |  |  |  |
| Plaster profile<br>53656070               |  |  |  |  |
| Surface-mounted profile<br>53603070       |  |  |  |  |
| LED surface-mounted profile<br>53606070   |  |  |  |  |
| Surface-mounted profile, high<br>53381302 |  |  |  |  |