




ALTERO-R LED recessed downlight, TunableWhite, IP44
 Article no. 12035854TW



Tender
 LED recessed downlight, TunableWhite, IP44, Round. Toolless ceiling installation by installation springs. Ceiling cut-out Ø 68 mm, Installation depth 72 mm, Outer diameter 83 mm, Weight 0,241 kg, Reflector silver with rotationssymmetrical, deep, wide distributed light intensity. Cover glass transparent Luminous flux 510 - 610 lm, Power 1 x 9 W, Light colour warm white to daylight white, Correlated color temperature (CCT) 2.700 - 6.500 K, Colour rendering index CRI > 90, Housing material: Aluminium / Glass / Plastic, Colour: black structure / gold structure, Permissible ambient temperature (ta): -20 °C up to +25 °C, Protection class (EN 61140): III, Degree of protection (DIN EN 60529): IP44. For connection to an external driver, which is not included in the scope of delivery of the luminaire. Depending on driver dimmable.

Product Benefits

- Modular product series with a wide range of colors.
- For flexible lighting solutions for changing room concepts from neutral to accentuated.
- Available in the color temperatures 3,000 K and 4,000 K and dim2warm (3,000 K - 1,800 K), TunableWhite (2,700 K - 6,500 K) and 2,700 K.
- Standard ceiling cut-out 68 mm.
- Recessed light emission.
- IP44 protection rating for installation in closed ceilings.
- Also available in square design.


ALTERO-R LED recessed downlight, TunableWhite, IP44

Article no. 12035854TW

Article data	
Article no.	12035854TW
GTIN	4251433981893
Series name	ALTERO-R
Short description	LED recessed downlight, TunableWhite, IP44
Material	Aluminium / Glass / Plastic
Colour	black structure / gold structure
Type of surface	Structure
Shape	Round
Outer diameter	83 mm
Built-in diameter min.	68 mm
Built-in diameter max.	68 mm
Installation depth	72 mm
Hight	3 mm
Weight	0.241 kg
D licence plate	No
Conformance	CE, UKCA

Lighting technology	
Colour temperature	2.700 K - 6.500 K
Light colour	white
Color Temperature 1	2,700 K
Color Temperature 2	6,500 K
Light output	Direct
Luminous flux	510 - 610 lm
Luminous flux 1	510 lm
Luminous flux 2	610 lm
System efficiency	68 lm/W
Colour rendering	CRI > 90
Reflector	Faceted
Reflector colour	silver
Beam angle	33°
Light sharing	Symmetric
Adjustable color temperature	Infinite control

Operating technology of the luminaire	
Voltage type	DC
Current	500 mA
Lamp	LED
Protection class	III
Protection class on the ceiling side	IP20
Degree of protection	IP44
Dimmable	Depending on type of control gear
Control	Depending on driver
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Energy efficiency class	not required

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Max. ceiling thickness	35 mm
Further references	No cover with thermal insulation material
Material cover	Glass transparent


ALTERO-R LED recessed downlight, TunableWhite, IP44
 Article no. 12035854TW

Packing data	
Gross weight	0.291 kg
Length of packaging	100 mm
Packaging width	100 mm
Packaging height	100 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>

Required accessories
<p>Article no.: 17821010</p> <p>LED converter 500 mA, TunableWhite, DALI-DT8 dimmable, 15 W</p> <p>Power: 3 - 15 W, ohne Konfektionierung</p> <p>Dimensions: 178 mm x 46 mm x 22 mm</p> <p>https://www.brumberg.com/fileadmin/products/Datenblatt_17821010_2021_DE.pdf</p>

Optional accessories
<p>Article no.: 83331000</p> <p>Connection box 230 V AC, 5-pole (DALI / 1-10 V)</p> <p>Dimensions: 90 mm x 52 mm x 30 mm</p> <p>https://www.brumberg.com/fileadmin/products/Datenblatt_83331000_2021_DE.pdf</p>
<p>Article no.: 81201180</p> <p>Reducing ring D 110 mm, for luminaire cut-out size 68 mm</p> <p>Dimensions: 110 mm</p> <p>https://www.brumberg.com/fileadmin/products/Datenblatt_81201180_2021_DE.pdf</p>
<p>Article no.: 81202180</p> <p>Reducing ring D 130 mm, for luminaire cut-out size 68 mm</p> <p>Dimensions: 130 mm</p> <p>https://www.brumberg.com/fileadmin/products/Datenblatt_81202180_2021_DE.pdf</p>
<p>Article no.: 81203180</p> <p>Reducing ring D 145 mm, for luminaire cut-out size 68 mm</p> <p>Dimensions: 145 mm</p> <p>https://www.brumberg.com/fileadmin/products/Datenblatt_81203180_2021_DE.pdf</p>