




ALOR LED bollard light, IP65, height 600 mm
 Article no. 60046103



Tender
 LED bollard luminaire, IP44, 2CCT, height 600 mm, luminaire width 95 mm, height 600 mm, weight 3 kg, with rotationally symmetrical narrow-wide beam light distribution. Transparent glass cover, rated luminous flux 516 lm, rated wattage 1 x 6 W, warm white light color, most similar color temperature (CCT) 3,000 K, general color rendering index CRI > 80, housing material: aluminum / glass, color: graphite structure, permissible ambient temperature (ta): -20 °C - +25 °C, protection class (EN 61140): I, degree of protection (DIN EN 60529): IP44. For connection to an external control gear, which is not included with the luminaire. switchable.

| Article data | |
|-------------------|--|
| Article no. | 60046103 |
| GTIN | 4255752501800 |
| Series name | ALOR |
| Short description | LED bollard light, IP65, height 600 mm |
| Material | Aluminium / Glass |
| Colour | graphite structure |
| Shape | Other |
| Width | 95 mm |
| Height | 600 mm |
| Scope of delivery | incl. converter for connection to 230 V mains voltage, switchable and connection box with through-wiring |
| Weight | 3 kg |
| Conformance | CE, UKCA |


ALOR LED bollard light, IP65, height 600 mm

Article no. 60046103

| Lighting technology | |
|---------------------|-------------------|
| Colour temperature | 2.700 K / 3.000 K |
| Light colour | white |
| Light output | Direct |
| Luminous flux | 516 lm |
| System efficiency | 86 lm/W |
| Colour rendering | CRI > 80 |
| Light sharing | Symmetric |

| Operating technology of the luminaire | |
|---------------------------------------|--|
| System output | 6 W |
| Voltage type | AC |
| AC nominal voltage max | 230 V |
| Frequency max | 50 Hz |
| Lamp | LED |
| Protection class | I |
| Degree of protection | IP44 |
| Control | on/off |
| Bulb change possible | The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person. |
| Energy efficiency class | not required |

| Mounting technology | |
|-----------------------|-------------------|
| Mounting method | Surface mounting |
| Place of installation | Floor-mounted |
| Material cover | Glass transparent |

| Packing data | |
|-------------------------|---|
| Gross weight | 3.2 kg |
| Length of packaging | 220 mm |
| Packaging width | 220 mm |
| Packaging height | 675 mm |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |