






ABACO-S LED recessed spotlight set, DALI dimmable, IP44

Article no. 41415173


Tender

LED recessed spotlight set, DALI dimmable, IP44. Toolless ceiling installation by installation springs. Ceiling cut-out Ø 68 mm, Installation depth 38 mm, Length 83 mm, Width 83 mm, Weight 0,18 kg, with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, transparent. Luminous flux 1.010 lm, Power 1 x 8 W, Light colour warm white, Correlated color temperature (CCT) 3.000 K, Colour rendering index CRI 82, Rated life time L80/B50 at 25 °C: 50.000 h, Housing material: Aluminium / PMMA, Colour: white structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP44. For connection to an external driver, which is not included in the scope of delivery of the luminaire. DALI-2 dimmable.

Product Benefits

- Protection class IP44 for the application location normal area to Damp indoor area
- Standard ceiling cut-out 68 mm - low installation depth 38 mm
- Dimmable as standard via trailing edge phase control (supplied as a set)
- Above-average luminous flux output with 1,010 lumens for the system the system (126 lm/W).


ABACO-S LED recessed spotlight set, DALI dimmable, IP44

Article no. 41415173

Article data	
Article no.	41415173
GTIN	4255752500117
Series name	ABACO-S
Short description	LED recessed spotlight set, DALI dimmable, IP44
Material	Aluminium / PMMA
Colour	white structure
Type of surface	Structure
Shape	Square
Length	83 mm
Width	83 mm
Built-in diameter	68 mm
Installation depth	38 mm
Hight	3 mm
Scope of delivery	incl. connection box, 5-pole for through-wiring
Weight	0.18 kg
Conformance	CE, UKCA

Lighting technology	
Colour temperature	3.000 K
Light colour	white
Light output	Direct
Luminous flux	1,010 lm
System efficiency	126 lm/W
Colour rendering	CRI 82
Reflector	Faceted
Reflector colour	silver
Beam angle	36°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	8 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Protection class	II
Protection class on the ceiling side	IP20
Degree of protection	IP44
Dimmable	Yes
Control	DALI-2
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L80/B50 at 25 °C	50.000 h
Energy efficiency class	not required

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Pivoted
Swivel angle	15°
Max. ceiling thickness	25 mm
Further references	No cover with thermal insulation material
Material cover	Plastic, transparent
Circlip	Without circlip
Suitable for through-wiring	Yes



ABACO-S LED recessed spotlight set, DALI dimmable, IP44
Article no. 41415173

Packing data	
Gross weight	0.24 kg
Length of packaging	105 mm
Packaging width	105 mm
Packaging hight	90 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Optional accessories	
Article no.: 5327	
Leaf spring set	
https://www.brumberg.com/fileadmin/products/Datenblatt_00532700_2021_DE.pdf	