




KACIE MAXI LED Surface-mounted downlight, DALI dimmable

Article no. 12597174DA


Tender

LED Surface-mounted downlight, DALI dimmable, Round. Luminaire diameter 230.0 mm, Height 150.0 mm Weight 2.868 kg, Reflector silver with rotationssymmetrical, deep, wide distributed light intensity.. Luminous flux 4.665 lm, UGR < 21, Power 1 x 48 W, Light colour neutral white, Correlated color temprature (CCT) 4.000 K, Colour rendering index CRI > 90, Rated life time L70/B10 at 25 °C: 50.000 h, Rated life time L70/B50 at 25 °C: 50.000 h, Housing material: Aluminium / Plastic, Colour: white structure, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP20. With electronic driver, DALI-2 dimmable.

Product Benefits

- Round surface-mounted downlight made of solid aluminum with generously dimensioned heat management.
- High-quality reflector.
- Simple installation.
- CRI > 90, UGR < 21.
- Available in switchable and DALI dimmable versions.


KACIE MAXI LED Surface-mounted downlight, DALI dimmable

Article no. 12597174DA

Article data	
Article no.	12597174DA
GTIN	4251433999737
Series name	KACIE MAXI
Short description	LED Surface-mounted downlight, DALI dimmable
Material	Aluminium / Plastic
Colour	white structure
Type of surface	Structure
Shape	Round
Outer diameter	230 mm
Hight	150 mm
Scope of delivery	incl. converter for connection to 230 V mains voltage, DALI-2 dimmable
Weight	2.868 kg
D licence plate	No
Conformance	CE, UKCA

Lighting technology	
Colour temperature	4.000 K
Light colour	white
Light output	Direct
Luminous flux	4,665 lm
System efficiency	97 lm/W
Colour rendering	CRI > 90
Reflector	Faceted
Reflector colour	silver
Beam angle	70°
Glare evaluation	UGR < 21
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	48 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP20
Dimmable	Yes
Control	DALI-2
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L70/B50 at 25 °C	50,000 h
Energy efficiency class	not required

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Material cover	Without cover



KACIE MAXI LED Surface-mounted downlight, DALI dimmable
Article no. 12597174DA

Packing data	
Gross weight	3.112 kg
Length of packaging	255 mm
Packaging width	235 mm
Packaging hight	200 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.