






QUALITYFLEX Protection Horizon LED flex board 5 m, CRI >90, 5 W / m, IP67

Article no. 19582503



Tender

LED flex board 5 m, CRI >90, 5 W / m, IP67, white, Light colour: white, 3.000K, CRI > 90. Length: 5000 mm . Lamp power per meter: 5.0 W/m, Luminous flux per meter: 156.0 lm/m, Degree of protection: IP67, Protection class: III, Voltage: 24V DC, Beam angle: 120.0 °, 120 LEDs per meter, Chip distance (Short Pitch) : 8,33mm. For individual application, the LED flex board can be used all 50 mm be cut back. If the LED flex board is shortened, the IP protection must be restored by the customer. The maximum system length of 27.000 mm must not be exceeded with one feed-in.

Product Benefits

- Suitable for indoor and outdoor applications (IP67).
- Can be divided every 50 mm (protection class IP65).
- Ideal for terraces, facades and entrance areas.
- Available lengths 5 m, 10 m or 27 m.
- Maximum length with one feed: 27,000 mm.
- Service life L80/B10: 36,000 hours.
- Simple installation with matching aluminum profiles or fixing clips.
- Dimmable with appropriate accessories.


QUALITYFLEX Protection Horizon LED flex board 5 m, CRI >90, 5 W / m, IP67

Article no. 19582503

Article data	
Article no.	19582503
GTIN	4251433998884
Series name	QUALITYFLEX Protection Horizon
Short description	LED flex board 5 m, CRI >90, 5 W / m, IP67
Colour	white
Length	5,000 mm
Width	12 mm
Hight	20 mm
Scope of delivery	incl. 1 x assembly instructions
Weight	3.04 kg
Length of the connection line	1,000 mm
Conformance	CE, UKCA

Lighting technology	
Colour temperature	3.000 K
Light colour	white
Luminous flux per meter	156 lm/m
System efficiency	31 lm/W
McAdam-Step	McAdam-Step 2
Colour rendering	CRI > 90
Beam angle	120°
Adjustable color temperature	No

Operating technology of the luminaire	
Lamp power per meter	5 W/m
Voltage type	DC
DC nominal voltage max	24 V
Lamp	LED
Protection class	III
Degree of protection	IP67
Ambient temperature	-20°C up to +50°C
Dimmable	Yes
Wire number	2
Control	Depending on driver
Length of the connection line	1,000 mm
Cable assignment	red = + pole black = - pole
Design of the connecting cable	one-sided
Bulb change possible	No
Rated life time L70/B50 at 25 °C	54,000 h
Rated life time L80/B10 at 25 °C	36.000 h
Energy efficiency class	E

Operating technology of QualityFlex	
Power per meter	5 W/m
Short Pitch	8.33 mm
Number of lamps per meter	120 Qty
Length of individual sections	50 mm
Smallest bend radius	120 mm
Length	5,000 mm
Maximum module length	27,000 mm
Circuit type	Parallel conduction
LED Type	2835 LED


QUALITYFLEX Protection Horizon LED flex board 5 m, CRI >90, 5 W / m, IP67

Article no. 19582503

Packing data	
Gross weight	3.3 kg
Length of packaging	400 mm
Packaging width	400 mm
Packaging height	150 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Compatible Driver						
Article no.						
17206000						
17207000						
17214000						
17223000						
17224000						
17225000						
17226000						
17227000						
17228000						
17230000	5 W	30 W	Trailing-edge phase	145 mm	50 mm	22 mm
17231000	12 W	75 W	Trailing-edge phase	185 mm	60 mm	31 mm
17232000	12 W	120 W	Trailing-edge phase	223 mm	64 mm	32 mm
17240000	1 W	20 W	on/off	150 mm	40 mm	30 mm
17241000	1 W	40 W	on/off	210 mm	40 mm	30 mm
17242000	1 W	60 W	on/off	250 mm	40 mm	30 mm
17243000	1 W	120 W	on/off	300 mm	40 mm	30 mm
17244000	1 W	150 W	on/off	310 mm	40 mm	30 mm
17250000	1 W	45 W	DALI-2	187 mm	45 mm	31 mm
17251000	1 W	80 W	DALI-2	290 mm	45 mm	31 mm
17252000	1 W	150 W	DALI-2	290 mm	45 mm	31 mm
17260000						

Compatible Controller						
Article no.		Power	Control	Length	Width	Height
17502000	1 W	120 W	DALI	183 mm	33 mm	23 mm
18151000	1 W	240 W	KNX	170 mm	59 mm	30 mm
18152000	1 W	240 W	DALI-DT6	170 mm	59 mm	30 mm
18153000	1 W	240 W	DMX	170 mm	59 mm	30 mm
18154000	1 W	240 W	1-10 V	170 mm	59 mm	30 mm
18161000	1 W	240 W	KNX	72 mm	90 mm	70 mm
18162000	1 W	240 W	DALI-DT6	54 mm	110 mm	66 mm
18164000	1 W	240 W	1-10 V	54 mm	110 mm	66 mm
17528000	120 W	240 W	Wireless technology control	145 mm	46.5 mm	16 mm
17511000	120 W	240 W	Wireless technology control	145 mm	46.5 mm	16 mm
18157000	1 W	240 W	ZigBee	145 mm	46.5 mm	16 mm
18192000	1 W	240 W	Wireless technology control	160 mm	45 mm	18 mm



QUALITYFLEX Protection Horizon LED flex board 5 m, CRI >90, 5 W / m, IP67
Article no. 19582503

Compatible Profiles				
Short description	Series name	Length	Width	Hight
Mounting profile 53581260	QUALITYFLEX Protection Ho- rizon	1,000 mm	17.5 mm	22.9 mm
Bendable add-on profile, 500 mm 53582260	QUALITYFLEX Protection Ho- rizon	5 14 mm	13.5 mm	18 mm