




**SOL MIDI MULTIPOWER LED highbay luminaire, dali dimmable**  
 Article no. 78313084

**Tender**

LED highbay luminaire, dali dimmable, Round. Luminaire diameter 300.0 mm, Height 195.0 mm, Weight 3.5 kg, with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, transparent. Luminous flux 26.100 lm, Power 1 x 160 W, Light colour neutral white, Correlated color temperature (CCT) 4.000 K, Colour rendering index CRI > 80, Rated life time L70/B50 at 25 °C: 50.000 h, Rated life time L80/B50 at 25 °C: 50.000 h, Housing material: Aluminium / Polycarbonate, Colour: black, Permissible ambient temperature (ta): -25 to +45°C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP65, shock resistance according to IEC62262: IK09. With electronic driver, DALI-2 dimmable.

**Product Benefits**

- 5 years Brumberg light warranty.
- D mark.
- Dip switches for multilumen: 160 / 130 / 110 / 85 W.
- Long life: L80B50 >50,000 h at 25 °C.
- High luminous efficacy.
- Dimmable as standard: DALI-2.
- Wide range of accessories.
- Protection class: IP65.
- Low maintenance lighting realization.
- Ambient temperature range: -25 °C to +45 °C.


**SOL MIDI MULTIPOWER LED highbay luminaire, dali dimmable**

Article no. 78313084

| Bestromung | Leistung | Lichtstrom | 1   | 2   | 3   |
|------------|----------|------------|-----|-----|-----|
| 340 mA     | 85 W     | 14.300 lm  | Aus | Aus | Aus |
| 420 mA     | 110 W    | 17.900 lm  | Aus | Aus | An  |
| 500 mA     | 130 W    | 21.200 lm  | Aus | An  | Aus |
| 620 mA     | 160 W    | 26.100 lm  | An  | Aus | Aus |

| Article data                  |   |
|-------------------------------|---|
| Article no.                   | 78313084  |
| GTIN                          | 4251433994572   |
| Series name                   | SOL MIDI MULTIPOWER   |
| Short description             | LED highbay luminaire, dali dimmable  |
| Material                      | Aluminium / Polycarbonate   |
| Colour                        | black   |
| Shape                         | Round   |
| Outer diameter                | 300 mm  |
| Height                        | 195 mm  |
| Scope of delivery             | Delivery: incl. screwable fixing eye, shrink end caps on the DALI cable and connection cable 1,500 mm |
| Weight                        | 3.5 kg  |
| Length of the connection line | 1,500 mm  |
| stamp                         | D-Kennzeichen   |
| Conformance                   | CE, UKCA  |

| Lighting technology          |               |
|------------------------------|---------------|
| Colour temperature           | 4.000 K       |
| Light colour                 | white         |
| Light output                 | Direct        |
| Luminous flux                | 26,100 lm     |
| System efficiency            | 163 lm/W      |
| McAdam-Step                  | McAdam-Step 4 |
| Colour rendering             | CRI > 80      |
| Luminaire optics             | Lens          |
| Reflector                    | Without       |
| Beam angle                   | 120°          |
| Light sharing                | Symmetric     |
| Adjustable color temperature | No            |


**SOL MIDI MULTIPOWER LED highbay luminaire, dali dimmable**

Article no. 78313084

| Operating technology of the luminaire |  |
|---------------------------------------|--|
| Voltage type                          | AC/DC  |
| AC nominal voltage min                | 100 V  |
| AC nominal voltage max                | 277 V  |
| DC nominal voltage min                | 141 V  |
| DC nominal voltage max                | 276 V  |
| Frequency max                         | 60 Hz  |
| Frequency min                         | 50 Hz  |
| Lamp                                  | LED  |
| Lamp holder                           | Without fitting  |
| Protection class                      | I  |
| Degree of protection                  | IP65   |
| Ambient temperature                   | -25 to +45 °C  |
| Dimmable                              | Yes  |
| Control                               | DALI-2   |
| Minimum / maximum dimming range       | 10 - 100 %   |
| Length of the connection line         | 1,500 mm   |
| Design of the connecting cable        | Unilateral   |
| Bulb change possible                  | The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person. |
| Rated life time L70/B50 at 25 °C      | 50,000 h   |
| Rated life time L80/B50 at 25 °C      | 50.000 h   |
| Energy efficiency class               | not required   |
| max. no. lights on B16 A              | 14   |
| max. no. lights on C10 A              | 9  |
| max. no. lights on C16 A              | 15   |

| Mounting technology         |                                |
|-----------------------------|--------------------------------|
| Mounting method             | Suspended                      |
| Place of installation       | Ceiling-mounted                |
| Adjustability               | Not adjustable                 |
| Impact resistance           | IK09                           |
| Material cover              | Plastic, transparent           |
| Suitable for through-wiring | Yes, with optional accessories |

| Packing data            |   |
|-------------------------|---|
| Gross weight            | 4.1 kg  |
| Length of packaging     | 305 mm  |
| Packaging width         | 180 mm  |
| Packaging height        | 345 mm  |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.<br>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |


**SOL MIDI MULTIPOWER LED highbay luminaire, dali dimmable**

Article no. 78313084

| Optional accessories  |
|---|
| Article no.: 81062000<br>Change optics 60° to 78312<br><br><a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81062000_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81062000_2021_DE.pdf</a>  |
| Article no.: 81092000<br>Change optics 90° to 78312<br><br><a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81092000_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81092000_2021_DE.pdf</a>  |
| Article no.: 81046250<br>Aluminium luminaire shade to 78312<br><br>Dimensions: 370 mm x 140 mm<br><a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81046250_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81046250_2021_DE.pdf</a> |
| Article no.: 81048000<br>PC light shade for 78312<br><br>Dimensions: 410 mm x 185 mm<br><a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81048000_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81048000_2021_DE.pdf</a>           |
| Article no.: 81049080<br>Ceiling / wall bracket for 78310 / 78311 / 78312<br><br><a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81049080_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81049080_2021_DE.pdf</a>                  |
| Article no.: 81051000<br>Chain suspension, 1000 mm<br><br><a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81051000_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81051000_2021_DE.pdf</a>   |
| Article no.: 81052000<br>Chain suspension, 2,000 mm<br><br><a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81052000_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81052000_2021_DE.pdf</a>  |
| Article no.: 81053000<br>Chain suspension, 3000 mm<br><br><a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81053000_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81053000_2021_DE.pdf</a>   |
| Article no.: 81055000<br>Chain suspension, 5000 mm<br><br><a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81055000_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81055000_2021_DE.pdf</a>   |
| Article no.: 81057000<br>Cable connector, 3-pin, IP68, black<br><br>Dimensions: 125 mm<br><a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81057000_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81057000_2021_DE.pdf</a>         |



**SOL MIDI MULTIPOWER LED highbay luminaire, dali dimmable**  
Article no. 78313084

**Optional accessories**

Article no.: 81058000

Y-cable connector, 5-pole, IP68, black

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_81058000\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_81058000_2021_DE.pdf)

Article no.: 81050000

Reducer, NPT 3/4" on M10

Dimensions: 70 mm

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_81050000\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_81050000_2021_DE.pdf)