





**MUNA PRO MINI LED recessed downlight, 5CCT, UGR<19, DALI dimmable, reflector silver, faceted**  
Article no. 12764073



#### Tender

LED recessed downlight, 5CCT, UGR<19, DALI dimmable, reflector silver, faceted, Round. Toolless ceiling installation by installation springs. Ceiling cut-out Ø 155 mm, Installation depth 100 mm, Outer diameter 174 mm, Weight 0,633 kg, Reflector silver with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, structured Luminous flux 1.750 - 2.100 lm, UGR < 19, Power 1 x 20 W, Light colour warm white to daylight white, Correlated color temperature (CCT) 2.700 - 5.700 K, Colour rendering index CRI > 90, Rated life time L70/B10 at 25 °C: 80.000 h, Rated life time L80/B50 at 25 °C: 50.000 h, Housing material: Aluminium / Polycarbonate / Steel, Colour: white matt, Permissible ambient temperature (ta): -20 °C up to +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20. With electronic driver, DALI-2 dimmable.



**MUNA PRO MINI LED recessed downlight, 5CCT, UGR<19, DALI dimmable, reflector silver, faceted**  
 Article no. 12764073

**Product Benefits**

- Round recessed downlight made of aluminum with generously dimensioned thermal management.
- 3CCT: 3,000 K, 4,000 K or 5,700 K adjustable.
- High-quality aluminum reflector with lens.
- Simple and tool-free installation.
- UGR < 19.
- Low installation depth of 130 mm, diameter of 280 mm, Ceiling cut-out 240-255 mm.
- Phase section dimmable.
- Cover ring removable and replaceable with black ring (separate accessory).
- Ring in round black or round white also with additional, suspended float glass (partially frosted) (separate accessory).
- Cover frame also available in square in black or white instead of round instead of round (separate accessories).

Article data	
Article no.	12764073
GTIN	4255752524724
Series name	MUNA PRO MINI
Short description	LED recessed downlight, 5CCT, UGR<19, DALI dimmable, reflector silver, faceted
Material	Aluminium / Polycarbonate / Steel
Colour	white matt
Type of surface	Matt
Shape	Round
Outer diameter	174 mm
Built-in diameter min.	145 mm
Built-in diameter max.	155 mm
Installation depth	100 mm
Hight	6.5 mm
Scope of delivery	inkl. Konverter mit vergrößertem Anschlussraum zur Durchgangsverdrahtung an 230 V-Netzspannung, DALI dimmbar mit Schalter zur Farbtemperatúrauswahl: 2.700 K / 3.000 K / 3.500 K / 4.000 K / 5.700 K
Weight	0.633 kg
D licence plate	No
stamp	EL
Conformance	CE, UKCA



**MUNA PRO MINI LED recessed downlight, 5CCT, UGR<19, DALI dimmable, reflector silver, faceted**  
Article no. 12764073

Lighting technology	
Colour temperature	2.700 K / 3.000 K / 3.500 K / 4.000 K / 5.700 K
Light colour	white
Color Temperature 1	2,700 K
Color Temperature 2	3,000 K
Color Temperature 3	3,500 K
Color Temperature 4	4,000 K
Farbtemperatur 5	5,700 K
Light output	Direct
Luminous flux	1,750 - 2,100 lm
Luminous flux 1	1,750 lm
Luminous flux 2	1,780 lm
Luminous flux 3	1,870 lm
Luminous flux 4	1,930 lm
Lichtstrom 5	2,100 lm
System efficiency	105 lm/W
Colour rendering	CRI > 90
Reflector	Faceted
Reflector colour	silver
Beam angle	60°
Glare evaluation	UGR < 19
Light sharing	Symmetric
Adjustable color temperature	Stages

Operating technology of the luminaire	
System output	20 W
Voltage type	AC/DC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Lamp holder	Without fitting
Protection class	II
Degree of protection	IP20
Dimmable	Yes
Control	DALI-2
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L80/B50 at 25 °C	50.000 h
Energy efficiency class	not required

Mounting technology	
Mounting method	Recessed mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Max. ceiling thickness	25 mm
Further references	No cover with thermal insulation material
Material cover	Plastic, structured
Suitable for through-wiring	Yes



**MUNA PRO MINI LED recessed downlight, 5CCT, UGR<19, DALI dimmable, reflector silver, faceted**  
Article no. 12764073

Packing data	
Gross weight	0.794 kg
Length of packaging	240 mm
Packaging width	190 mm
Packaging height	125 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Optional accessories	
Article no.: 81216070 Cover frame, square, for 12564	
Dimensions: 174 mm x 174 mm x 6.5 mm <a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81216070_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81216070_2021_DE.pdf</a>	
Article no.: 81216080 Cover frame, square, for 12564	
Dimensions: 174 mm x 174 mm x 6.5 mm <a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81216080_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81216080_2021_DE.pdf</a>	
Article no.: 81211080 Cover ring, round, for 12564	
Dimensions: 174 mm x 6.5 mm <a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81211080_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81211080_2021_DE.pdf</a>	
Article no.: 81221070 Cover ring, round, with suspended float glass, partially frosted, for 12564	
Dimensions: 174 mm x 25 mm <a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81221070_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81221070_2021_DE.pdf</a>	
Article no.: 81221080 Cover ring, round, with suspended float glass, partially frosted, for 12564	
Dimensions: 174 mm x 25 mm <a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81221080_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81221080_2021_DE.pdf</a>	
Article no.: 81230070 Surface-mounted housing, round, for 12564	
Dimensions: 182 mm x 155 mm <a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81230070_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81230070_2021_DE.pdf</a>	
Article no.: 81230080 Surface-mounted housing, round, for 12564	
Dimensions: 182 mm x 155 mm <a href="https://www.brumberg.com/fileadmin/products/Datenblatt_81230080_2021_DE.pdf">https://www.brumberg.com/fileadmin/products/Datenblatt_81230080_2021_DE.pdf</a>	