

Datenblatt Art. 333.616

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

19" Steckdosenleiste 1HE

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung Frequenz	16A / 250V~ 50 Hz	Rated current / rated voltage Frequency	16A / 250V~ 50 Hz
Netzanschluss		Power supply	
Zuleitung Farbe Zuleitung	2,0m H05VV-F 3G1,5mm² schwarz	Supply cable Colour supply cable	2,0m H05VV-F 3G1,5mm² black
Stecker Steckertyp	CEE 7/7 (Type E/F) Winkelstecker	Plug Plug type	CEE 7/7 (Type E/F) Right angled plug
Stromausgang		Power output	
Steckdosen 12x IEC60320 C13 2-polig mit Schutzkontakt Schwarz, ähnlich RAL 9005, 90° 10A 250V~,IP20 mit Verriegelungsabdeckung		Socket outlets 12x IEC60320 C13 2-pole with earthing contact Black, similar to RAL 9005, 90° 10A 250V~,IP20 with locking cap	
Weitere Produkteigenschaften		Further product attributes	
Abmessungen Plattform	438,5x44x47mm 1 HE	Dimensions Plattform	438,5x44x47mm 1 HE
Material Gehäuse: Aluminium, eloxiert		Material Housing: Aluminium, anodised	
Abdeckung: PA6 GF30 850°C, schwarz ähnlich RAL 9005		Cover: PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang 1x Steckdosenleiste ALU 1HE 19" 2x 19" Befestigungswinkel (lose beigelegt) inkl. Verriegelungslaschen rot		Scope of delivery 1x Power strip Alu 1U 19" 2x 19" mounting brackets (enclosed separately) incl. protective tongue for interlock red	
Im Polybeutel		Packed in polybag	
Umgebungsbedingungen		Environmental conditions	
Schutzart	IP20	Protection type	IP20

