




EVIE MIDI LED surface-mounted / recessed panel, power adjustable to 20 W, 15 W or 10 W, color temperature adjustable between 3,000 K and 4,000 K via DIP switch.

Article no. 12741073



BRUMBERG
Light. Since 1873.



Tender

LED surface-mounted / recessed panel, power adjustable to 20 W, 15 W or 10 W, color temperature adjustable between 3,000 K and 4,000 K via DIP switch. Round. Toolless ceiling installation by installation springs. Ceiling cut-out Ø 205 mm, Installation depth 29 mm, Outer diameter 225 mm, Weight 0,5 kg, with rotationssymmetrical, deep, wide distributed light intensity. Cover PMMA. Luminous flux 2.230 - 2.400 lm, UGR < 25, Power 1 x 20 W, Light colour warm white to neutral white, Correlated color temperature (CCT) 3.000 - 4.000 K, Colour rendering index CRI > 80, Rated life time L70/B50 at 25 °C: 102.000 h, Housing material: Polycarbonate, Colour: white matt, Permissible ambient temperature (ta): -20 °C up to +40 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP44, shock resistance according to IEC62262: IK03. With electronic driver, DIP-Switch dimmable. Additionally this luminaire is ENEC-proofed by an independent laboratory.

Product Benefits

- Adjustable power via DIP switches, three levels.
- Adjustable color temperature via DIP switches: 3,000 K and 4,000 K.
- Quick installation via through-wiring, including strain relief.
- Can be used as a recessed or surface-mounted fixture.
- Light guide and cover made of PMMA.
- Up to 127 lm per watt.
- Housing with a predetermined break point on the side for cable entry.

EVIE MIDI LED surface-mounted / recessed panel, power adjustable to 20 W, 15 W or 10 W, color temperature adjustable between 3,000 K and 4,000 K via DIP switch.

Article no. 12741073



BRUMBERG

Light. Since 1873.

Farbtemperatur	Leistung	Lichtstrom
3.000 K	20 W	2.230 lm
4.000 K	20 W	2.400 lm
3.000 K	15 W	1.790 lm
4.000 K	15 W	1.820 lm
3.000 K	10 W	1.155 lm
4.000 K	10 W	1.200 lm

Article data	
Article no.	12741073
GTIN	4255752529712
Series name	EVIE MIDI
Short description	LED surface-mounted / recessed panel, power adjustable to 20 W, 15 W or 10 W, color temperature adjustable between 3,000 K and 4,000 K via DIP switch.
Material	Polycarbonate
Colour	white matt
Type of surface	Matt
Shape	Round
Outer diameter	225 mm
Built-in diameter min.	60 mm
Built-in diameter max.	205 mm
Installation depth	29 mm
Hight	25 mm
Scope of delivery	1 Stück Montagebügel 2 Stück Federn 3 Stück Schrauben, PWA4 x 25 mm 3 Stück Dübel, Ø 6 x 30 mm 1 Stück Sicherungsseil
Weight	0.5 kg
D licence plate	No
stamp	ENEC
Conformance	CE, UKCA

Lighting technology	
Colour temperature	3.000 K / 4.000 K
Light colour	white
Color Temperature 1	3,000 K
Color Temperature 2	4,000 K
Light output	Direct
Luminous flux	2,230 - 2,400 lm
Luminous flux 1	2,230 lm
Luminous flux 2	2,400 lm
System efficiency	120 lm/W
McAdam-Step	McAdam-Step 3
Colour rendering	CRI > 80
Reflector	Without
Beam angle	106°
Glare evaluation	UGR < 25
Light sharing	Symmetric
Adjustable color temperature	Stages

EVIE MIDI LED surface-mounted / recessed panel, power adjustable to 20 W, 15 W or 10 W, color temperature adjustable between 3,000 K and 4,000 K via DIP switch.

Article no. 12741073



BRUMBERG
Light. Since 1873.

Operating technology of the luminaire	
Voltage type	AC/DC
AC nominal voltage min	176 V
AC nominal voltage max	265 V
DC nominal voltage min	195 V
DC nominal voltage max	278 V
Frequency max	60 Hz
Frequency min	50 Hz
Lamp	LED
Lamp holder	LED
Protection class	II
Protection class on the ceiling side	IP20
Degree of protection	IP44
Ambient temperature	-20°C up to +40°C
Dimmable	No
Control	DIP-Switch
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L70/B50 at 25 °C	102,000 h
max. no. lights on B16 A	26
max. no. lights on C10 A	23
max. no. lights on C16 A	37

Operating technology of driver	
Operating technology of driver	
AC nominal voltage min	176 V
AC nominal voltage max	265 V
Frequency min	50 Hz
Frequency max	60 Hz
DC nominal voltage min	195 V
DC nominal voltage max	278 V
Protection class	II
Degree of protection	IP44
Power min.	10 W
Power max.	20 W
Suitable for emergency lighting	No
Ambient temperature	-20 up to 40 °C
max. no. lights on B10 A	20
max. no. lights on B16 A	26
max. no. lights on C16 A	37
max. no. lights on C10 A	23
Flicker value Pst LM	1.00
Stroboscopic effect value SVM	.40
Control	DIP-Switch
Connection type-primary	Connection box
Number of poles	3
Flicker-free	Yes

EVIE MIDI LED surface-mounted / recessed panel, power adjustable to 20 W, 15 W or 10 W, color temperature adjustable between 3,000 K and 4,000 K via DIP switch.

Article no. 12741073



BRUMBERG
Light. Since 1873.

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Max. ceiling thickness	13 mm
Impact resistance	IK03
Further references	No cover with thermal insulation material
Cover	PMMA
Suitable for through-wiring	Yes

Packing data	
Gross weight	0.55 kg
Length of packaging	250 mm
Packaging width	230 mm
Packaging height	35 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Optional accessories