



Mechanical characteristics

cable group

interface dimensions acc. to assembly code
panel piercing
mating life

Components

centre contact
outer contact
tooth washer
other metal parts
insulator
gasket
o-ring

Electrical characteristics

impedance
frequency
voltage proof
insulation resistance
contact resistance
 centre contact
 outer contact

Environmental

operating temp.
RoHS compliant

Mechanische Eigenschaften

Kabelgruppe

Steckgesicht nach Montageanleitung
Montagebohrung
Steckzyklen

Bauteile

Innenkontakt
Außenkontakt
Fächerscheibe
sonstige Metallteile
Isolierung
Dichtung
O-Ring

Elektrische Eigenschaften

Wellenwiderstand
Frequenz
Prüfspannung
Isolationswiderstand
Durchgangswiderstand
 Innenkontakt
 Außenkontakt

Umgebung

Betriebstemperatur
RoHS konform

G 7: KX 22A, KX 3B, MRC 100 Flex (0.48L/1.5AF) Draka,
RG-174/U, RG-188A/U, RG-316/U
LMR-100A TMS
IEC 61169-8
A04
Z004
≥500

Materials / Material

CuBe2
CuZn39Pb3
CuSn6
CuZn39Pb3
PTFE
silicone / Silikon
NBR

Finish / Oberfläche

NiP-Au
Cu2Ni5
Cu2Ni5
Cu2Ni5

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]	
			gez./ drawn	05.01.2017	MA		
			gepr./ appr.	24.01.2017	BJ	ca./approx.	21,2
		Maßstab/ scale	Benennung/ title				
		2:1 (1:1)	BNC Bulkhead Jack BNC-Kabeleinbaubuchse				
		unt. Maß/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.			
			K	J01001A1318			
			Ersatz für/ replaces				
					Telegärtner		
					Maße/ dimensions: mm		
					Original : DIN A4		
					Blatt/ sheet 1 von/ of 1		