

Mechanical characteristics
cables

interface dimensions acc. to assembly code

Components

- centre contact
- outer contact
- crimp ferrule
- other metal parts
- insulator

Environmental

RoHS compliant

Mechanische Eigenschaften

Kabel

Steckgesicht nach Montageanleitung

Bauteile

- Innenkontakt
- Außenkontakt
- Crimprohr
- sonstige Metallteile
- Isolierung

Umgebung

RoHS konform

- (a) G 7: KX 22A, KX 3B; RG-174/U, RG-188A/U, RG-316/U, IEC 60169-17 A2505



Materials / Material

- CuZn39Pb3
- CuZn39Pb3
- CuZnPb2
- CuZn39Pb3
- PE-LD, POM

Finish / Oberfläche

- Cu1Ni2Au0.8
- Cu2Ni5
- Cu2Ni5
- Cu2Ni5

- (a) 2002/95/EC

1996	Datum/date	Name/name	Werkstoff/ material
	gez./drawn	07.08.	BI
Norm/stand.	gepr./appr.	08.08.96	BJ
	Oberfläche/ finish		
Maßstab/scale	Benennung/title		
2:1	TNC-Kabelstecker TNC-Straight-Plug		
untol. Maße/ dim. without tolerances according to	Untert./doc.type	Zeichnungsnr./drawing no.	
	K	J01010A0038	
a	22630	25.02.11	MA
			
 Maße/dimensions: mm			
Original: DIN A4			