

Mechanical characteristics
cables

interface dimensions acc. to assembly code
 centre conductor
 outer conductor
 mating life

Components

centre contact
 outer contact
 bayonet
 spring washer
 other metal parts
 insulator
 gasket

Electrical characteristics

impedance
 frequency
 return loss
 working voltage
 voltage proof
 insulation resistance
 contact resistance
 centre contact
 outer contact

Environmental

operating temp.
 protection class
 RoHS compliant

Mechanische Eigenschaften
Kabel

Steckgesicht nach Montageanleitung
 Innenleiter
 Außenleiter
 Steckzyklen

Bauteile

Innenkontakt
 Außenkontakt
 Bajonett
 Federscheibe
 sonstige Metallteile
 Isolierung
 Dichtung

Elektrische Eigenschaften

Wellenwiderstand
 Frequenz
 Rückflussdämpfung
 Betriebsspannung
 Prüfspannung
 Isolationswiderstand
 Durchgangswiderstand
 Innenkontakt
 Außenkontakt

Umgebung

Betriebstemperatur
 Schutzklasse
 RoHS konform

G37 : 2.7/7.3 AF, 2.7/7.3 CF, 213CRT7 LOW LOSS, 7810A, 9913, C2FCP, C2FP, CNT-400, EC 400, HPF 400, LMR-400, MRC 400 AFB, TZC 500 32, SPEEDFOAM 400 HFJ, WBC-400, WCX400
 G42 : 02Y (St) C (St) H 2.6/7.3 AF, 213RT5, 9914, H 1000, H2000, RT 50/20

Ⓐ G55: 9913F, MRC 400 Flex
 RG-213/U
 RG-214/U

IEC 61169-8
 D11
 solder / Löt
 clamp / Klemm
 >500

Materials / Material

brass / Messing
 brass / Messing
 zinc diecast / Zinkdruckguss
 copper alloy / Kupferlegierung
 brass / Messing
 PTFE
 silicone, NBR

Finish / Oberfläche


Cu1Ni2Au0.8
 Cu2Ni5
 Zn/Cu6Ni6
 Cu2Ni5
 CuSnZn3

50 Ω
 0 - 4 GHz Ⓐ
 typ.: 1 GHz -30 dB ; 2 GHz -26 dB ; 3 GHz -21dB

≤ 500 V_{eff} / 50 Hz
 1.5 kV_{eff} / 50 Hz
 ≥ 5 GΩ

≤ 20 mΩ
 ≤ 5 mΩ

Ⓐ 2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight (g)
				gepr./ appr	23.12.2010	PU	ca./approx.
				Maßstab/ scale	Benennung/ title		
				1:1	BNC Angle Plug BNC-Kabelwinkelstecker		
				untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.	
				K	J01000B1195		 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1
a				Ersatz für/ replaces	J01000A0029; J01000A1195		