

Mechanical characteristics

cables
interface dimensions acc. to assembly code

Components

centre contact
outer contact
other metal parts
insulator
gasket

Electrical characteristics

impedance
frequency
voltage proof
insulation resistance
contact resistance
 centre contact
 outer contact

Environmental

operating temp.
RoHS compliant

Mechanische Eigenschaften

Kabel
Steckgesicht nach Montageanleitung

Bauteile

Innenkontakt
Außenkontakt
sonstige Metallteile
Isolierung
Dichtung

Elektrische Eigenschaften

Wellenwiderstand
Frequenz
Prüfspannung
Isolationswiderstand
Durchgangswiderstand
 Innenkontakt
 Außenkontakt

Umgebung

Betriebstemperatur
RoHS konform

G 3: KX 21A, RG-178B/U, RG-196A/U
IEC 61169-8
A09


Materials / Material



CuBe2Pb
CuZn39Pb3
CuZn39Pb3
PTFE
silicone / Silikon

Finish / Oberfläche

NiP-Au
Cu2Ni5
Cu2Ni5

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight [g]
					04.01.2017	MA	
				gepr./ appr.	24.01.2017	BJ	ca./approx. 19
Maßstab/ scale				Benennung/ title			
2:1 (1:1)				BNC Straight Jack BNC-Kabelbuchse			
untl. Maße/ dim. without tolerances according to				Untert./ doc. type		Zeichnungsnr./ drawing no.	
				K		J01001A0033	
				Ersatz für/ replaces			
							
				 Maße/ dimensions: mm			
				Original : DIN A4			
				Blatt/ sheet 1 von/ of 1			