



Mechanical characteristics

cable group

interface dimensions acc. to assembly code
 panel piercing
 centre conductor
 outer conductor
 mating life

Components

centre contact
 outer contact
 tooth washer
 crimp ferrule
 other metal parts
 insulator
 gasket

Electrical characteristics

impedance
 frequency
 voltage proof
 insulation resistance
 contact resistance
 centre contact
 outer contact

Environmental

operating temp.
 RoHS compliant

Mechanische Eigenschaften

Kabelgruppe

Steckgesicht nach Montageanleitung
 Montagebohrung
 Innenleiter
 Außenleiter
 Steckzyklen

Bauteile

Innenkontakt
 Außenkontakt
 Fächerscheibe
 Crimprohr
 sonstige Metallteile
 Isolierung
 Isolierflansch

Elektrische Eigenschaften

Wellenwiderstand
 Frequenz
 Prüfspannung
 Isolationswiderstand
 Durchgangswiderstand
 Innenkontakt
 Außenkontakt

Umgebung

Betriebstemperatur
 RoHS konform

G 1: 7806A Belden, 9907 Belden, KX 15, CNT-195 Andrew, LMR-195 TMS, HPF 195 Harbour Industries, RG-58C/U, WCX195 NEK/CDT

IEC 61169-8
 A1305
 Z004
 crimp
 crimp
 ≥500

Materials / Material

CuNi1Pb1P (C97)
 CuZn39Pb3
 CuSn6
 Cu SF w
 CuZn39Pb3
 PE-LD
 POM

Finish / Oberfläche

NiP-Au
 Cu2Ni5
 Cu2Ni5
 Ni5
 Cu2Ni5

50 Ω
 0-4 GHz
 1,5kV_{eff} / 50 Hz
 ≥ 5 GΩ
 < 20 mΩ
 ≤ 5 mΩ

-30°C / +75°C
 2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name		Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn	18.10.2016	MA		
			gepr./ appr.	18.11.2016	KL	ca./approx.	14
Maßstab/ scale		Benennung/ title					
2:1 (1:1)		BNC Bulkhead Jack BNC-Kabeleinbaubuchse					
untst. Maße/ dim. without tolerances according to		Untert./ doc. type		Zeichnungsnr./ drawing no.			
		K		J01001A0056			
		Ersatz für/ replaces					
					Maße/ dimensions: mm		
					Original : DIN A4		
					Blatt/ sheet 1 von/ of 1		