

Mechanical characteristics
interface dimensions acc. to

Mechanische Eigenschaften
Steckgesicht nach

BNC - IEC 61169-8
F - IEC 61169-24

Components
center contact
outer contact
insulator

Bauteile
Innenkontakt
Außenkontakt
Isolierung

Materials / Material
brass / Messing
brass / Messing
PTFE

Finish / Oberfläche
gold plated / vergoldet
nickel plated / vernickelt

Electrical characteristics
frequency
insulation resistance
contact resistance
center contact
outer contact



Elektrische Eigenschaften
Frequenz
Isolationswiderstand
Durchgangswiderstand
Innenkontakt
Außenkontakt

0-1 GHz
≥ 5 MΩ
≤ 1.5 mΩ
≤ 1.0 mΩ

Environmental
RoHS compliant

Umgebung
RoHS konform

2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight (g)
					07.10.2013	MA	
				gepr./ appr.	07.10.2013	BJ	ca./approx.
				Maßstab/ scale	Benennung/ title		
				2:1	Adapter BNC-F (f-f) Adapter BNC-F (f-f)		
				Unterl. Maße/ dim. without tolerances according to	Unterl./ doc. type	Zeichnungsnr./ drawing no.	
				K	J01008A0021		
				Ersatz für/ replaces			
							 Maße/ dimensions: mm
							Blatt/ sheet 1 von/ of 1