

**Mechanical characteristics**  
cables

interface dimensions acc. to assembly code

- Components**  
 centre contact  
 outer contact  
 other metal parts  
 insulator  
 gasket

- Electrical characteristics**  
 impedance  
 frequency  
 working voltage  
 voltage proof  
 insulation resistance  
 contact resistance  
 center contact  
 outer contact

- Environmental**  
 operating temp.  
 RoHS compliant

**Mechanische Eigenschaften**  
Kabel

Steckgesicht nach Montageanleitung

- Bauteile**  
 Innenkontakt  
 Außenkontakt  
 sonstige Metallteile  
 Isolierung  
 Dichtung

- Elektrische Eigenschaften**  
 Wellenwiderstand  
 Frequenz  
 Betriebsspannung  
 Prüfspannung  
 Isolationswiderstand  
 Durchgangswiderstand  
 Innenkontakt  
 Außenkontakt

- Umgebung**  
 Betriebstemperatur  
 RoHS konform


G 2: 0.6/3.7; 0.6L/3.7; 0.6L/3.7AF Draka; 3C-2V; 75022 V(0.6L/3.7) Sytronic Kabel GmbH; 75060 V(0.6/3.7) Sytronic Kabel GmbH; 8241 Belden; KX 6A; RG-59B/U; VK95 0.6/3.7 Percon

IEC 60169-17  
A08



- |                             |                            |
|-----------------------------|----------------------------|
| <b>Materials / Material</b> | <b>Finish / Oberfläche</b> |
| CuNi1Pb1P (C97)             | NiP-Au                     |
| CuZn39Pb3                   | Cu2Ni5                     |
| CuZn39Pb3                   | Cu2Ni5                     |
| PE-LD                       |                            |
| NBR                         |                            |

- 75 Ω  
 0-11 GHz  
 ≤ 500 V<sub>eff</sub> / 50 Hz  
 1,5 kV<sub>eff</sub> / 50 Hz  
 ≥ 5 GΩ  
 ≤ 10 mΩ  
 ≤ 2,5 mΩ

-30°C / +75°C  
 2011/65/EU



M 1:1

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]	
			gez./ drawn	20.10.2016	MA		
			gepr./ appr.	22.11.2016	KL	ca./approx. 13	
			Maßstab/ scale	Benennung/ title			
			2:1 (1:1)	TNC Straight Jack TNC-Kabelbuchse			
			Untert./ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.		 Maße/ dimensions: mm
			K	J01013A0004			
			Ersatz für/ replaces			Original : DIN A4	
					Blatt/ sheet 1 von/ of 1		