

Mechanical characteristics
cable group

interface dimensions acc. to assembly code
centre conductor
outer conductor
mating life

Components

centre contact
crimp ferrule
other metal parts
insulator

Electrical characteristics

impedance
frequency
voltage proof
insulation resistance
contact resistance
centre contact
outer contact

Environmental

operating temp.
RoHS compliant

Mechanische Eigenschaften
Kabelgruppe

Steckgesicht nach Montageanleitung
Innenleiter
Außenleiter
Steckzyklen

Bauteile

Innenkontakt
Crimprohr
sonstige Metallteile
Isolierung

Elektrische Eigenschaften

Wellenwiderstand
Frequenz
Prüfspannung
Isolationswiderstand
Durchgangswiderstand
Innenkontakt
Außenkontakt

Umgebung

Betriebstemperatur
RoHS konform

G 2: 0.6/3.7; 0.6L/3.7; 0.6L/3.7AF Draka; 3C-2V; 75022 V(0.6L/3.7) Sytronic Kabel GmbH; 75060 V(0.6/3.7) Sytronic Kabel GmbH; 8241 Belden; KX 6A; RG-59B/U; VK95 0.6/3.7 Percon


IEC 60169-17
A0831
Crimp
Crimp
>500

Materials / Material


CuNi1Pb1P (C97)
Cu SF w
CuZn39Pb3
PE-LD

Finish / Oberfläche

NiP Au
Ni5
Cu2Ni5



M 1:1

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn	24.10.2016	MA	
			gepr./ appr.	23.11.2016	KL	ca./approx. 12
			Maßstab/ scale	Benennung/ title		
			2:1 (1:1)	TNC Straight Jack TNC-Kabelbuchse		
			untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.	
				K	J01013A2262	Maße/ dimensions: mm
			Ersatz für/ replaces			Original : DIN A4
					Blatt/ sheet 1 von/ of 1	