

Mechanical characteristics
cable group

interface dimensions acc. to assembly code
panel piercing

- Components**
 centre contact
 outer contact
 tooth washer
 other metal parts
 crimp ferrule
 insulator
 o-ring

Electrical characteristics

- impedance
 frequency
 return loss
 voltage proof
 insulation resistance
 contact resistance
 centre contact
 outer contact

- Environmental**
 operating temp.
 RoHS compliant

Mechanische Eigenschaften
Kabelgruppe

Steckgesicht nach Montageanleitung
Montagebohrung

- Bauteile**
 Innenkontakt
 Außenkontakt
 Fächerscheibe
 sonstige Metallteile
 Crimprohr
 Isolierung
 O-Ring

Elektrische Eigenschaften

- Wellenwiderstand
 Frequenz
 Rückflussdämpfung
 Prüfspannung
 Isolationswiderstand
 Durchgangswiderstand
 Innenkontakt
 Außenkontakt

- Umgebung**
 Betriebstemperatur
 RoHS konform

- G 4: 0.3LS/1.7S; 1520A Belden; 1521A Belden; 1522A Belden; 179DT Belden; RG-179B/U; RG-187A/U
 0.36L/1.6 Medialine Highflex Sommer;
 0.38L/1.6 2x 75 Ohm Cinemax Sommer;
 0.38L/1.7 RGB Multicore Obelisk MKII Sommer


- IEC 60169-17
 A2903
 Z004

- Materials / Material**
 CuNi1Pb1P (C97)
 CuZn39Pb3
 CuSn6
 CuZn39Pb3
 SF Cu w
 PTFE
 NBR

- Finish / Oberfläche**
 NiP-Au
 Cu2Ni5
 Cu2Ni5
 Cu2Ni5
 Ni5

- 75 Ω
 typ.: 1 GHz-26 dB; 4 GHz-10 dB
 0-4 GHz
 1,5kV_{eff} / 50 Hz
 ≥ 5 GΩ
 ≤ 20 mΩ
 ≤ 5 mΩ

- 30°C / +85°C
 2011/65/EU



M 1:1

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn	24.10.2016	MA	
			gepr./ appr.	23.11.2016	KL	ca./approx. 21
Maßstab/ scale 2:1 (1:1)			Benennung/ title TNC Bulkhead Jack TNC-Kabeleinbaubuchse			
untst. Maße/ dim. without tolerances according to			Untert./ doc. type K	Zeichnungsnr./ drawing no. J01013B0008		
Ersatz für/ replaces						
					Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1	