

Mechanical characteristics

cable group

interface dimensions acc. to assembly code
 centre conductor
 outer conductor
 mating life
 coupling torque

Components

centre contact
 other metal parts
 insulator
 gasket

Electrical characteristics

impedance
 return loss

voltage proof
 insulation resistance
 contact resistance
 centre contact
 outer contact

Environmental

RoHS compliant

Mechanische Eigenschaften

Kabelgruppe

Steckgesicht nach Montageanleitung
 Innenleiter
 Außenleiter
 Steckzyklen
 Kupplungsdrehmoment

Bauteile

Innenkontakt
 sonstige Metallteile
 Isolierung
 Dichtung

Elektrische Eigenschaften

Wellenwiderstand
 Rückflussdämpfung

Prüfspannung
 Isolationswiderstand
 Durchgangswiderstand
 Innenkontakt
 Außenkontakt

Umgebung

RoHS konform

G36: 5062 1/4" Eupen, HPL 50-1/4 Acome, LCF 14-50 J RFS

IEC 61169-16
 B25
 clamp / klemm
 clamp / klemm
 >500
 4-6 Nm

Materials / Material



CuZn39Pb3
 CuZn39Pb3
 PTFE
 MVQ

Finish / Oberfläche

Cu2Ag5
 Cu2Ag3

50 Ω
 typ.: 1 GHz - 30 dB; 2 GHz - 30 dB;
 3 GHz - 23,5dB
 2,5 kV_{eff} / 50 Hz
 ≥ 5 GΩ
 ≥ 1,5 mΩ
 ≥ 1,0 mΩ

2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight (g)
			gez./ drawn	04.04.2013	MA	
			gepr./ appr	05.04.2013	BJ	ca./approx.
			Maßstab/ scale	Benennung/ title		
			2:1	N Straight Jack N-Kabelbuchse		
			untot. Maße/ dim. without tolerances according to	Unterl./ doc. type	Zeichnungsnr./ drawing no.	
				K	J01021A0043	 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1
			Ersatz für/ replaces			