


with label /  
mit Aufkleber



**Mechanical characteristics**

cables  
 interface dimensions acc. to  
 assembly code  
     centre conductor  
     outer conductor  
 mating life  
 coupling torque  
**Components**  
 centre contact  
 outer contact  
 other metal parts  
 crimp ferrule  
 insulator  
 gasket

**Electrical characteristics**

impedance  
 frequency  
 return loss  
  
 voltage proof  
 insulation resistance  
 power  
 contact resistance  
     centre contact  
     outer contact

**Environmental**

operating temp.  
 RoHS compliant

**Mechanische Eigenschaften**

Kabel  
 Steckgesicht nach ...  
 Montageanleitung  
     Innenleiter  
     Außenleiter  
 Steckzyklen  
 Kupplungsdrehmoment  
**Bauteile**  
 Innenkontakt  
 Außenkontakt  
 sonstige Metallteile  
 Crimprohr  
 Isolierung  
 Dichtung

**Elektrische Eigenschaften**

Wellenwiderstand  
 Frequenz  
 Rückflussdämpfung  
  
 Prüfspannung  
 Isolationswiderstand  
 Leistungsübertragung  
 Durchgangswiderstand  
     Innenkontakt  
     Außenkontakt

**Umgebung**

Betriebstemperatur  
 RoHS konform

K 07252 D-01; RG-214/U; RG-393/U  
 IEC 61169-4  
 D0512  
 solder / Löt  
 Crimp  
 >500  
 25-35 Nm

**Materials / Material**

brass / Messing  
 brass / Messing  
 brass / Messing  
 copper / Kupfer  
 PTFE  
 silicone / Silikon

**Finish / Oberfläche**

Cu2Ag5  
 CuSnZn3  
 CuSnZn3  
 CuSnZn3

50 Ω  
 0-3 GHz  
 typ.: 1 GHz - 30 dB; 2 GHz - 24 dB;  
       3 GHz - 22 dB

(a) 2.7 kV<sub>eff</sub> / 50 Hz  
 ≥ 10 GΩ  
 ≤ 1.8 kW / 1 GHz

≤ 0.4 mΩ  
 ≤ 0.2 mΩ

-40°C / 85°C  
 2002/95/EC

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn	30.01.2006	GE	
			gepr./ appr	12.02.2008	GB	co./approx.
			Maßstab/ scale	Benennung/ title		
			1:1	7-16 Angle Plug 7-16-Kabelwinkelstecker		
			untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.	
				K	J01120C0010	Maße/ dimensions: mm Original : DIN A4
a	25162	05.09.2013	MA	Ersatz für/ replaces	J01120A0010	Blatt/ sheet 1 von/ of 1