

Mechanical characteristics
cable group

Mechanische Eigenschaften
Kabelgruppe

G 2: 0.6/3.7; 0.6L/3.7; 0.6L/3.7AF Draka; 3C-2V;
75022 V(0.6L/3.7) Sytronic Kabel GmbH;
75060 V(0.6/3.7) Sytronic Kabel GmbH;
8241 Belden; KX 6A; RG-59B/U;
VK95 0.6/3.7 Percon

interface dimensions acc. to
assembly code
centre conductor
outer conductor

Steckgesicht nach
Montageanleitung
Innenleiter
Außenleiter

IEC 60169-12
B0631
crimp
crimp

Components
centre contact
outer contact
other metal parts
crimp ferrule
insulator

Bauteile
Innenkontakt
Außenkontakt
sonstige Metallteile
Crimprohr
Isolierung

Materials / Material
CuZn38Pb2
CuZn39Pb3
CuZn39Pb3
SF Cu w
POM

Finish / Oberfläche
Cu2Ag5
Cu2Ni5
Cu2Ni5
Ni5

Electrical characteristics
impedance
voltage proof
contact resistance
centre contact
outer contact

Elektrische Eigenschaften
Wellenwiderstand
Prüfspannung
Durchgangswiderstand
Innenkontakt
Außenkontakt


50 Ω
2 kV_{eff} / 50 Hz
≤ 5 mΩ
≤ 5 mΩ


Environmental
RoHS compliant

Umgebung
RoHS konform

2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]		
			gez./ drawn	02.11.2016	MA			
			gepr./ appr	23.11.2016	KL	ca./approx. 21		
			Maßstab/ scale 2:1 (1:1)	Benennung/ title UHF Straight Plug UHF-Kabelstecker				
			untol. Maße/ dim. without tolerances according to	Untert./ doc. type K	Zeichnungsnr./ drawing no. J01040A0000			
			Ersatz für/ replaces				Original : DIN A4	Blatt/ sheet 1 von/ of 1