



Baustellen-Bodenstrahler 50W



4 046725 357872

Leistungsmerkmale

Mit den beiden neuen Baustellen-Bodenstrahlern in 30 W und 50 W erweitern wir die FLUXX[®]-Serie von RED. Die lichtstarken LED-Baustellen-Bodenstrahler sind dank verstellbarer Achse eine mobile Lichtquelle, mit der man gezielt beleuchten kann. Die Strahler sind aus Aluminiumdruckguss, korrosionsbeständig sowie pulverbeschichtet in der Farbe Rot.

Die neuen Baustrahler der Serie FLUXX[®] besitzen eine 5-jährige Garantiezeit sowie eine Lebensdauer von 50.000 Stunden. Weiterhin zeichnet die Strahler wieder eine hohe Schaltfestigkeit aus sowie eine Farbwiedergabe von >70 Ra. Abstrahlwinkel: 130°.

Expertentipp

Die beiden Strahler haben eine Zuleitung von 3 m sowie zusätzlich eine Steckdose und zwei USB-Ladeanschlüsse.

DEHA Nummer

5105190

Artikelnummer

5610-20-0004

EAN-Nummer

4046725357872

Kennzeichnung

	lm	K	CRI	IP
50.000h	4.300	6.500	>70	54

ROT

Allgemeine Daten

Elektrische Daten	
Eingangsspannung	180 - 265 V AC
Stromart	Wechselstrom (AC)
Netzfrequenz	50/60 Hz
Lichttechnische Daten	
Farbwiedergabeindex	> 70 Ra
Abstrahlwinkel	130°
Lichtstrom	4.300 lm
Lichtquelle	Nicht auswechselbares LED-Modul
Aufwärmzeit (60%)	< 2,0 Sek
Startzeit	< 0,5 Sek
Zusätzliche Daten	
Arbeitstemperaturbereich	-20 bis +45°C
Lagertemperaturbereich	-30 bis +60°C
Nennlebensdauer	50.000h
Anzahl der Schaltzyklen	200.000
Schutzart	IP54
Garantie	5 Jahre
Gehäusematerial	Aluminium Druckguss
Gehäusefarbe	Rot
LED Abdeckung	Klar
Zuleitung	3,0 m
Weitere Anschlussmöglichkeiten	230V AC Steckdose + zwei 5 V 2,1 A USB-Anschlüsse

Spezifische Daten

LED Arbeitsleuchte 50W	
Nennleistung	50 W
Farbtemperatur	6.500 K
Abmessung	352 x 185 x 365 mm

Bestelldaten

DEHA-Nummer	Typ	Art.Nr.	EAN	Farbe	VPE
5105190	LED FLUXX [®] 50 W	5610-20-0004	4046725357872	rot	1 Stk.



4 046725 357872

Performance features

We are expanding the RED FLUXX[®] series with the two new 30 W and 50 W construction site LED spots. Thanks to their adjustable axis, the bright LED construction site ground spotlights are a mobile light source that can be used for targeted illumination. The spotlights are made of die-cast aluminium, corrosion-resistant and powder-coated in red.

The new construction floodlights of the FLUXX[®] series have a 5-year guarantee and a service life of 50,000 hours. Furthermore, LED spots are characterised by high switching resistance and colour rendering of >70 Ra. Beam angle: 130°.

Expert's Tip

The two spotlights have a 3 m supply cable as well as an additional socket and an USB charging connection.

DEHA number

5105190

Article number

5610-20-0004

EAN number

4046725357872

Labels

	lm	K	CRI	IP
50.000h	4.300	6.500	>70	54

ROT

General data

Input voltage	180 - 265 V AC
Current type	Alternating current (AC)
Power frequency	50/60 Hz

Lighting data

Colour rendering index	> 70 Ra
Beam angle	130°
Luminous flux	4.300lm ± 10%
Light source	Alternating current
Warm-up time (60%)	< 2,0 Sek
Starting time	< 0,5 Sek

Additional data

Operating temperature range	-20 to +45°C
Storage temperature range	-30 to +60°C
Nominal service life	50.000h
Number of switching cycles	200.000
Degree of protection	IP54
Guarantee Housing material	5 Years
Colour	Die-cast aluminium
LED cover	Red
Supply cable	Clear
Durthier connection options	3m
	230V AC socket + zwei 5V 2,1A USB connection

Specific data

LED work light 50W

Rated power	50W
FColour temperature	6.500K
Dimensions	352 x 185 x 365mm

Order data

DEHA-Number	Typ	EAN	Colour	VPE
5105190	Construction site LED spot 50W	4046725357872	red	1 Pc.