

DOI Document Nu	mber .	UCCE-14-18		
		St	andard & product range.	
YSLY.				
_				
	Sr.	Number of Cores	Conductor Size	
	1	3	0.5 mm2-16mm2	
	2	4	0.5 mm2-16mm2	
	3	5	0.5 mm2-16mm2	
	4	6	1.5 mm2	
	5	7	0.5 mm2-16mm2	
	6	8	0.5 mm2-1.5mm2	
	7	9	0.75 mm2-1.5mm2	
	8 -	10	0.5 mm2-1.5mm2	
	9	11	1.5 mm2	
	10	12	0.5 mm2-2.5mm2	
	11	14	0.5 mm2-2.5mm2	
-	12	15	0.75 mm2	
	13	16	1.0 mm2-2.5mm2	
-	14	18	0.5 mm2-2.5mm2	
		19		
-	15		1.0 mm2	
-	16	20	1.0 mm2-2.5mm2	
Ļ	17	21	1.0 mm2-2.5mm2	
-	18	25	0.5 mm2-2.5mm2	
_	19	30	0.5 mm2-0.75mm2	
	20	32	1.5 mm2	
	21	34	0.5 mm2-2.5mm2	
	22	40	0.5 mm2-2.5mm2	
	23	41	1.0 mm2	
	24	42	0.5 mm2-2.5mm2	
	25	50	0.5 mm2-2.5mm2	
	26	61	0.5 mm2-2.5mm2	
	27	65	0.5 mm2-1.5mm2	
	28	80	1.5 mm2	
	29	100	1.5 mm2	
		Traceability of	each cable is followed by drum numb	pers
			ended Use of Product Type	
		Supply of electric	ity in buildings and other civil enginee	
	Work		limiting the generation and spread of f	
			fanufacturer Information	
<b>A</b>		UIC (United Industrie		•
Manufacturer	:	=EL SEWEDY CAB		*,
		Office: plot 27, 1st district.5th settlement, new Cairo.		
Factory Address		Tel: 72599732-27599733-27599734		
		WWW.ELSEWEDY.COM		
		Factory: 10th of Ramadan City Zone, A 3,		
			fax: (2015)411366 PO.Box: 1748 p	ost code: 10505
	Systen		ment and Verification of Constancy	
			System 3	
			Notified Body/laboratory	
		MADE SERVICE S		
			<u>BASEC</u> No. 2661	
			Performances Declared	
Essential Characteristic		Performance		Harmonized Technica
Danation to Ein-				Specification
Reaction to Fire		Eca		
Smoke Production				DN 60676 2014 A 2 201
Flaming Droplets		-		EN 50575:2014+A1:201
Acidity		NIDIO		
Dangerous substance			NPD	
The same			sued under the responsibility of the i	1

Quality Assurance Manager