

Datenblatt Art. 396.184

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

Profi-Kabeltrommel Leertrommel 3-fach

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung	für Leitung bis max. 40m H07RN-F 3G1,5mm ²	Supply cable	for supply cable max. 40m H07RN-F 3G1,5mm ²
Stromausgang		Power output	
Steckdosen		Socket outlets	
3x CEE 7/3 (Type F)		3x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Schwarz, ähnlich RAL 9005, 35° mit		Black, similar to RAL 9005, 35° with lid, red	
Klappeckel, rot		16A / 250V~, IP20	
16A / 250V~, IP44			
Schutzeinrichtungen		Protective devices	
Thermoschutzschalter	1-polig, rückstellbar	Thermo circuit breaker	1-pole, resettable
Weitere Produkteigenschaften		Further product attributes	
Scheibendurchmesser	280mm	disc diameter	280mm
Material	Doppelrohrgestell	Material	double tubular frame
Trommelkörper aus bruchfestem		Cable drum special plastic material	
Spezialkunststoff			
Lieferumfang	1x Profi-Kabeltrommel Leertrommel	Scope of delivery	1x Cable-drum without lead
Im Karton		In carton	
Umgebungsbedingungen		Environmental conditions	
Schutzart	IP44	Protection type	IP44
Konformität / Approbation		Conformity / Approval	

Bauart geprüft

DGUV-I 203-006

Type approved

DGUV-I 203-006

