

Datenblatt Art. 940.041

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

Patch Leitung

Produkteigenschaften		Product attributes	
Länge (L)	5,0m	Length (L)	5,0m
Außendurchmesser (AD)	6,2mm	Outer diameter (OT)	6,2mm
Kabeltyp	S/FTP CAT.6	Cabletyp	S/FTP CAT.6
Mantelisoliation	4x2xAWG27 LSZH	Sheath insulation	4x2xAWG27 LSZH
Farbe Mantelisoliation	PVC	Colour Sheath insulation	PVC
halogenfrei	grau	halogenfree	grey
flammwidrig		flame-retardant	
Seite 1		Side 1	
Stecker mit Knickschutztülle Kontakte	RJ45, geschirmt vergoldet	Plug with strain relief sleeve Contact	RJ45, shielded gold-plated
Seite 2		Side 2	
Stecker mit Knickschutztülle Kontakte	RJ45, geschirmt vergoldet	Plug with strain relief sleeve Contacts	RJ45, shielded gold-plated
Biegeradius min.	31mm	Bending radius min.	31mm
Lieferumfang 1x Patch Leitung		Scope of delivery 1x patch cable	
Im Polybeutel		Packed in polybag	
Umgebungsbedingungen		Environmental conditions	
Umgebungstemperatur bei Montage und Nutzung	0°C – 60°C	Surrounding temperature during mounting and use	0°C – 60°C
Konformität / Approbation		Conformity / Approval	
Bauart geprüft	IEC-60332-1; ISO/IEC 11801 & EN50173-1 TIA/EIA 568.2-1	Type approved	IEC-60332-1; ISO/IEC 11801 & EN50173-1 TIA/EIA 568.2-1

