

Han HC-AX-PE-Kontaktbuchse



Part number	09 11 000 6256
Specification	Han HC-AX-PE-Kontaktbuchse
HARTING eCatalogue	https://b2b.harting.com/09110006256

Identification

Category	Contacts
Series	TC 350
Type of contact	Axial screw contact
Description of the contactPE contact	

Version

Gender Female

Technical characteristics

Conductor cross-section	35 70 mm²
Operating current	≤350 A
Contact resistance	≤0.2 mΩ
Limiting temperature	-40 +125 °C
Stripping length	19 20 mm
Mating cycles	≥500

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
RoHS	compliant with exemption
RoHS exemptions	6a: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight 6c: Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead



Specifications and approvals

Specifications	EN 60664-1
	IEC 61984

Commercial data

Packaging size	1
Net weight	146.04 g
Country of origin	Romania
European customs tariff number	85359000