

## Han Brid-Wanddurchf.+ Cu-Bus Bu-c (G)



Part number	09 12 006 2794
Specification	Han Brid-Wanddurchf.+ Cu-Bus Bu-c (G)
HARTING eCatalogue	<a href="https://b2b.harting.com/09120062794">https://b2b.harting.com/09120062794</a>

### Identification

Category	Inserts
Series	Han-Brid <sup>®</sup>
Identification	Han-Brid <sup>®</sup> Cu
Element	Panel feed through

### Version

Gender	Female
Size	3 A
Number of contacts	2
Additional contacts	+ 4 electrical contacts 10 A + option for PE

### Technical characteristics

Rated current	10 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Insulation resistance	$\geq 10^{10} \Omega$
Limiting temperature	-40 ... +125 °C
Mating cycles	$\geq 500$

### Material properties

Material (insert)	Polycarbonate
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6c: Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50



Pushing Performance

## Material properties

REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

## Specifications and approvals

Specifications	IEC 61984
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076

## Commercial data

Packaging size	10
Net weight	16.36 g
Country of origin	Germany
European customs tariff number	85366990