

Han Brid-sti-c + Cu-Bus-sti-c (K)



Part number	09 12 006 3001
Specification	Han Brid-sti-c + Cu-Bus-sti-c (K)
HARTING eCatalogue	https://b2b.harting.com/09120063001

Identification

Category	Inserts
Series	Han-Brid [®]
Identification	Han-Brid [®] Cu
Specification	Hybrid field bus connector

Version

Gender	Male
Size	3 A
Number of contacts	2
Additional contacts	+ 4 electrical contacts 10 A + option for PE
Details	Cable side

Technical characteristics

Rated current	10 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Insulation resistance	$\geq 10^{10} \Omega$
Limiting temperature	-40 ... +125 °C
Mating cycles	≥ 500

Material properties

Material (insert)	Polycarbonate
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e



Pushing Performance

Material properties

REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

Specifications	IEC 61984
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076

Commercial data

Packaging size	10
Net weight	13.14 g
Country of origin	Germany
European customs tariff number	85366990