

Han USB module, male screw terminal



Part number	09 14 001 4651
Specification	Han USB module, male screw terminal
HARTING eCatalogue	https://b2b.harting.com/09140014651
Identification	
Category	Modules
Series	Han-Modular [®]
Type of module	Han [®] USB module
Description of the modulefor screw termination	

Version

Termination method	Screw termination
Gender	Male
Number of contacts	4
Details	USB 2.0

Technical characteristics

Conductor cross-section	0.14 0.5 mm²
Rated current	1 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	30 V
Insulation resistance	≥10 ¹⁰ Ω
Limiting temperature	-40 +85 °C
Stripping length	4.5 mm
Tightening torque	0.12 Nm
Mating cycles	≥500

Material properties

Material (insert)	Polycarbonate
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0

Page 1 / 2 | Creation date 2019-02-05 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

Specifications	EN 60664-1 IEC 60352-4
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076

Commercial data

Packaging size	1
Net weight	21.96 g
Country of origin	Germany
European customs tariff number	85389099