

# Han 3A-AK-Dichtung



Part number	09 20 003 5425	
Specification	Han 3A-AK-Dichtung	
HARTING eCatalogue	https://b2b.harting.com/09200035425	
Identification		
Category	Hoods/Housings	
Series of hoods/housings Han $A^{\textcircled{R}}$		
Type of hood/housing	Protection cover	
Description of hood/ housing	for bulkhead mounted housings	
	for surface mounted housings	
	Metal	
	With fixing cord	
	With seal	

### Version

Locking type	Single locking lever
Size	3 A
Field of application	Standard Hoods/housings for industrial applications
Details	for mounted female insert or for mounted Han-Brid <sup>®</sup> insert

### **Technical characteristics**

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP44 IP65 / IP67 with seal screw 09 20 000 9918
Type rating acc. to UL 50 / UL 50E	12

## Material properties

Material (seal)	NBR
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Page 1 / 2 | Creation date 2019-02-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



#### Specifications and approvals

Approvals	DNV GL
Commercial data	
Packaging size	10
Net weight	23.2 g
Country of origin	Romania
European customs tariff number	85389099