

Han A Hood Side Entry LC 2 Levers PG 21



| | |
|--------------------|---|
| Part number | 09 20 032 1530 |
| Specification | Han A Hood Side Entry LC 2 Levers PG 21 |
| HARTING eCatalogue | https://b2b.harting.com/09200321530 |

Identification

| | |
|--------------------------|------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han A® |
| Type of hood/housing | Hoods |
| Type | Low construction |

Version

| | |
|----------------------|---|
| Locking type | Double locking lever (on the hood) |
| Han-Easy Lock® | Yes |
| Size | 32 A |
| Version | Side entry |
| Cable entry | 1x Pg 21 |
| Field of application | Standard Hoods/housings for industrial applications |

Technical characteristics

| | |
|--|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| | |
|--|----------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |
| Material (locking) | Polycarbonate |
| | Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant |



Pushing Performance

Material properties

| | |
|-----------------------------|-----------|
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

Commercial data

| | |
|--------------------------------|----------|
| Packaging size | 1 |
| Net weight | 228.2 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |