

## Han B Hood Side Entry HC 4 Pegs PG 21



|                    |   |
|--------------------|---|
| Part number        | 09 30 010 0522  |
| Specification      | Han B Hood Side Entry HC 4 Pegs PG 21   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09300100522">https://b2b.harting.com/09300100522</a> |

### Identification

|                          |                    |
|--------------------------|--------------------|
| Category                 | Hoods/Housings     |
| Series of hoods/housings | Han <sup>®</sup> B |
| Type of hood/housing     | Hoods              |
| Type                     | High construction  |

### Version

|                      |   |
|----------------------|---|
| Locking type         | Double locking lever                              |
| Size                 | 10 B  |
| Version              | Side entry  |
| Cable entry          | 1x Pg 21  |
| Field of application | Standard hoods/housings for industrial connectors |

### Technical characteristics

|  |  |
|--|--|
| Limiting temperature                   | -40 ... +125 °C  |
| Degree of protection acc. to IEC 60529 | IP65<br>IP67 in combination with special bulkhead mounted housings |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12  |

### Material properties

|                             |                      |
|-----------------------------|----------------------|
| Material (hood/housing)     | Aluminium die-cast   |
| Surface (hood/housing)      | Powder-coated        |
| Colour (hood/housing)       | RAL 7037 (dust grey) |
| RoHS                        | compliant            |
| ELV status                  | compliant            |
| China RoHS                  | e                    |
| REACH Annex XVII substances | No                   |
| REACH ANNEX XIV substances  | No                   |



Pushing Performance

## Material properties

|                       |    |
|-----------------------|----|
| REACH SVHC substances | No |
|-----------------------|----|

## Specifications and approvals

|           |  |
|-----------|--|
| Approvals | DNV GL   |
| UL / CSA  | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |

## Commercial data

|                                |          |
|--------------------------------|----------|
| Packaging size                 | 1        |
| Net weight                     | 182.43 g |
| Country of origin              | Germany  |
| European customs tariff number | 85389099 |