

Han B Hood Coupler HC 2 Levers PG 21



| | |
|--------------------|---|
| Part number | 09 30 010 0732 |
| Specification | Han B Hood Coupler HC 2 Levers PG 21 |
| HARTING eCatalogue | https://b2b.harting.com/09300100732 |

Identification

| | |
|--------------------------|------------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han [®] B |
| Type of hood/housing | Cable to cable housing |
| Type | High construction |

Version

| | |
|----------------------------|---|
| Locking type | Double locking lever |
| Han-Easy Lock [®] | Yes |
| Size | 10 B |
| Version | Top entry |
| Cable entry | 1x Pg 21 |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| | |
|--|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| | |
|--|----------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |
| Material (seal) | NBR |
| Material (locking) | Polycarbonate |
| | Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |



Pushing Performance

Material properties

| | |
|-----------------------------|--|
| RoHS | compliant with exemption |
| RoHS exemptions | 6c: Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |

Specifications and approvals

| | |
|-----------|--|
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| | |
|--------------------------------|----------|
| Packaging size | 1 |
| Net weight | 223.7 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |