

Han 16B IP67 housing-SL-C



| Part number | 09 30 016 1308 |
|--------------------|-------------------------------------|
| Specification | Han 16B IP67 housing-SL-C |
| HARTING eCatalogue | https://b2b.harting.com/09300161308 |

Identification

| Category | Hoods/Housings |
|---------------------------------|---------------------------|
| Series of hoods/housings Han® B | |
| Type of hood/housing | Bulkhead mounted housings |
| Туре | Low construction |

Version

| Locking type | Single locking lever |
|----------------------------|---|
| Han-Easy Lock [®] | Yes |
| Size | 16 B |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|---------------|
| Degree of protection acc. to IEC 60529 | IP65 IP67 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|--|----------------------------------|
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |
| Material (seal) | NBR |
| Material (locking) | Polycarbonate Stainless steel |
| Colour (locking) | RAL 7037 (dust grey) |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant |



Material properties

| ELV status | compliant |
|-----------------------------|-----------|
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| Approvals | DNV GL |
|-----------|--|
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| Packaging size | 1 |
|--------------------------------|------------|
| Net weight | 124.1 g |
| Country of origin | China |
| European customs tariff number | 8538900000 |