

Han B Base Surface HC 1 Lever 2 Entries



| Part number | 09 30 048 0291 |
|--------------------|---|
| Specification | Han B Base Surface HC 1 Lever 2 Entries |
| HARTING eCatalogue | https://b2b.harting.com/09300480291 |

Identification

| Category | Hoods/Housings |
|---------------------------------|-------------------------|
| Series of hoods/housings Han® B | |
| Type of hood/housing | Surface mounted housing |
| Туре | High construction |

Version

| Locking type | Single locking lever |
|----------------------|---|
| Size | 48 B |
| Version | Side entry |
| Cable entry | 2x Pg 36 |
| Field of application | Standard hoods/housings for industrial connectors |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|-------------|
| Degree of protection acc. to IEC 60529 | IP65 |
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast |
|-----------------------------|----------------------|
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 7037 (dust grey) |
| Material (seal) | NBR |
| Material (locking) | Stainless steel |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | No |



Material properties

| REACH ANNEX XIV substances | No |
|----------------------------|----|
| REACH SVHC substances | No |

Specifications and approvals

| Approvals | DNV GL |
|-----------|--|
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| Packaging size | 1 |
|--------------------------------|-----------|
| Net weight | 1,175.3 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |