

Han C F crimp contact 4 mm² Au/HMC



| | |
|--------------------|---|
| Part number | 09 32 200 6229 |
| Specification | Han C F crimp contact 4 mm ² Au/HMC |
| HARTING eCatalogue | https://b2b.harting.com/09322006229 |

Identification

| | |
|-----------------|------------------------|
| Category | Contacts |
| Series | Han [®] C HMC |
| Type of contact | Crimp contact |

Version

| | |
|--------|--------|
| Gender | Female |
|--------|--------|

Technical characteristics

| | |
|---|-------------------|
| Conductor cross-section | 4 mm ² |
| Conductor cross-section | AWG 12 |
| Operating current | ≤40 A |
| Contact resistance | ≤1 mΩ |
| Stripping length | 9.5 mm |
| Mating cycles with other HMC components | ≥10,000 |

Material properties

| | |
|-----------------------------|--|
| Material (contacts) | Copper alloy |
| Surface (contacts) | HMC gold plated |
| RoHS | compliant with exemption |
| RoHS exemptions | 6c: Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |

Specifications and approvals

| | |
|----------------|------------|
| Specifications | EN 60664-1 |
|----------------|------------|



Pushing Performance

Specifications and approvals

| |
|-----------|
| IEC 61984 |
|-----------|

Commercial data

| | |
|--------------------------------|----------|
| Packaging size | 25 |
| Net weight | 2.5 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |