

Han 48B Ex-HBM-reel



Part number	09 36 048 0301
Specification	Han 48B Ex-HBM-reel
HARTING eCatalogue	https://b2b.harting.com/09360480301

Identification

Category	Hoods/Housings	
Series of hoods/housings Han® Ex		
Type of hood/housing	Bulkhead mounted housings	
Description of hood/ housing	With thermo-plastic cover	
Туре	Low construction	

Version

Locking type	Single locking lever
Size	48 B
Field of application	Connectors for explosion hazardous environments
Details	ATTENTION! Only to be used with Han® Ex inserts!

Technical characteristics

Limiting temperature	-20 +40 °C
Degree of protection acc. to IEC 60529	IP65 With cable gland

Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated Powder-coated
Colour (hood/housing)	RAL 5015 (sky blue)
Material (locking)	Stainless steel
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
REACH Annex XVII substances REACH ANNEX XIV substances	No No



Commercial data

Packaging size	1
Net weight	1,089 g
Country of origin	China
European customs tariff number	8538900000