

## Han Ex 4A-QL Kit HBM angled/HTE-M20



Part number	10 36 004 0005
Specification	Han Ex 4A-QL Kit HBM angled/HTE-M20
HARTING eCatalogue	<a href="https://b2b.harting.com/10360040005">https://b2b.harting.com/10360040005</a>

### Identification

Category	Connector set
Series	Han A <sup>®</sup>
Series of hoods/housings	Han <sup>®</sup> Ex

### Version

Termination method	Han-Quick Lock <sup>®</sup> termination
Locking type	Single locking lever
Size	3 A
Number of contacts	4
PE contact	Yes
Version	Top/side entry
Cable entry	1x M20
Field of application	Connectors for explosion hazardous environments

### Technical characteristics

Rated current	10 A
Rated voltage	90 V
Insulation resistance	$\geq 10^{10} \Omega$
Limiting temperature	-20 ... +40 °C
Mating cycles	$\geq 500$
Degree of protection acc. to IEC 60529	IP67 with seal screw 09 20 000 9918

### Material properties

Material (insert)	Polycarbonate
Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Uncoated
Colour (hood/housing)	RAL 5015 (sky blue)
Material (seal)	NBR



Pushing Performance

## Material properties

Material (locking) Stainless steel

Material flammability class acc. to UL 94 V-0

## Specifications and approvals

Specifications EN 60664-1  
IEC 61984  
EN 60079-0  
EN 60079-11

## Commercial data

Packaging size 1

Net weight 157.14 g

Country of origin Germany

European customs tariff number 85366990