

## Han-Yellock shell top entry M40



Part number	11 12 600 1403
Specification	Han-Yellock shell top entry M40
HARTING eCatalogue	<a href="https://b2b.harting.com/11126001403">https://b2b.harting.com/11126001403</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han-Yellock®
Type of hood/housing	Shell

### Version

Locking type	Push button
Size	Han-Yellock® 60
Version	Top entry
Cable entry	1x M40
Field of application	Hoods/housings for industrial applications

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Un-/locking temperature	-10 ... +85 °C
Degree of protection acc. to IEC 60529	IP65 IP67

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7021 (black grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No



Pushing Performance

## Specifications and approvals

Specifications	EN 60664-1
	IEC 61984
Approvals	DNV GL

## Commercial data

Packaging size	1
Net weight	143.8 g
Country of origin	Germany
European customs tariff number	85389099