

## Han 3A-HTE plastic (9-17mm)



|                    |   |
|--------------------|---|
| Part number        | 19 20 003 0410  |
| Specification      | Han 3A-HTE plastic (9-17mm)   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19200030410">https://b2b.harting.com/19200030410</a> |

### Identification

|                             |                             |
|-----------------------------|-----------------------------|
| Category                    | Hoods/Housings              |
| Series of hoods/housings    | Han A®                      |
| Type of hood/housing        | Hoods                       |
| Description of hood/housing | With integrated cable gland |

### Version

|                      |   |
|----------------------|---|
| Locking type         | Single locking lever                                |
| Size                 | 3 A   |
| Version              | Top entry   |
| Cable entry          | 1x Integrated                                       |
| Field of application | Standard Hoods/housings for industrial applications |

### Technical characteristics

|  |   |
|--|---|
| Limiting temperature                   | -40 ... +125 °C                             |
| Degree of protection acc. to IEC 60529 | IP44<br>IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12                               |
| Cable diameter                         | 9 ... 17 mm                                 |

### Material properties

|   |                        |
|---|------------------------|
| Material (hood/housing)                   | Polycarbonate          |
| Colour (hood/housing)                     | RAL 7032 (pebble grey) |
| Material flammability class acc. to UL 94 | V-0                    |
| RoHS                                      | compliant              |
| ELV status                                | compliant              |
| China RoHS                                | e                      |
| REACH Annex XVII substances               | No                     |



Pushing Performance

## Material properties

REACH ANNEX XIV substances No

REACH SVHC substances No

## Specifications and approvals

Approvals DNV GL

UL / CSA UL 1977 ECBT2.E235076  
CSA-C22.2 No. 182.3 ECBT8.E235076

## Commercial data

Packaging size 10

Net weight 8 g

Country of origin Germany

European customs tariff number 85389099

eCl@ss 27440202 Shell for industrial connectors