

## Han 6B-HMC-HSE-R-M20



Part number	19 30 206 1540
Specification	Han 6B-HMC-HSE-R-M20
HARTING eCatalogue	<a href="https://b2b.harting.com/19302061540">https://b2b.harting.com/19302061540</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> HMC
Type of hood/housing	Hoods
Type	Low construction

### Version

Locking type	Single locking lever
Size	6 B
Version	Side entry
Cable entry	1x M20
Field of application	Special hoods and housings for high mating cycles

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Mating cycles with other HMC components	≥10,000
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No



Pushing Performance

## Material properties

REACH SVHC substances	No
-----------------------	----

## Specifications and approvals

Approvals	DNV GL
-----------	--------

## Commercial data

Packaging size	1
----------------	---

Net weight	108.4 g
------------	---------

Country of origin	Germany
-------------------	---------

European customs tariff number	85389099
--------------------------------	----------