

Han 16B-HMC-gs-R-M32



Part number	19 30 216 0547	
Specification	Han 16B-HMC-gs-R-M32	
HARTING eCatalogue	https://b2b.harting.com/19302160547	
Identification		
Category	Hoods/Housings	
Series of hoods/housings Han [®] HMC		
Series of hoods/housing	gsHan [®] HMC	
Series of hoods/housing	gs Han [®] HMC Hoods	

Version

Locking type	Single locking lever
Size	16 B
Version	Side entry
Cable entry	1x M32
Field of application	Special hoods and housings for high mating cycles

Technical characteristics

Limiting temperature	-40 +125 °C
Mating cycles with other HMC components	≥10,000
Degree of protection acc. to IEC 60529	IP65
	4
Type rating acc. to UL 50 / UL 50E	4X
	12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No

Page 1 / 2 | Creation date 2019-02-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 19 30 216 0547 Han 16B-HMC-gs-R-M32



Material properties	
REACH SVHC substances	No
Specifications and approvals	
Approvals	DNV GL
Commercial data	
Packaging size	1
Net weight	222 g
Country of origin	Germany
European customs tariff number	85389099