

Han-Eco Mod.6-C-f. HBM/HSM-cord, lug



| | |
|--------------------|---|
| Part number | 19 41 006 5404 |
| Specification | Han-Eco Mod.6-C-f. HBM/HSM-cord, lug |
| HARTING eCatalogue | https://b2b.harting.com/19410065404 |

Identification

| | |
|---------------------------------|--|
| Category | Hoods/Housings |
| Series of hoods/housings | Han-Eco® Modular |
| Type of hood/housing | Protection cover |
| Description of hood/ housing | for bulkhead mounted housings |
| | for surface mounted housings |
| | for cable to cable housing With fixing cord |

Version

| | |
|--------------|----------------------|
| Locking type | Double locking lever |
| Size | 6 B |

Technical characteristics

| | |
|--|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Number of relockings | ≥500 |
| Degree of protection acc. to IEC 60529 | IP65 |

Material properties

| | |
|---|-------------------------------------|
| Material (hood/housing) | Polyamide Fibre-glass reinforced |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Specifications and approvals

| | |
|----------------|-----------|
| Specifications | IEC 61984 |
|----------------|-----------|



Pushing Performance

Specifications and approvals

| | |
|----------|--|
| | EN 45545-2 R22: HL1, HL2, HL3 |
| | EN 45545-2 R23: HL1, HL2, HL3 |
| | EN 45545-2 R24: HL1, HL2, HL3 |
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| | |
|--------------------------------|----------|
| Packaging size | 1 |
| Net weight | 41.6 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |