

# Han-Eco Mod.10-HSE-M32-glanded



Part number	19 41 110 0522	
Specification	Han-Eco Mod.10-HSE-M32-glanded	
HARTING eCatalogue	https://b2b.harting.com/19411100522	
Identification		
Category	Hoods/Housings	
Series of hoods/housingsHan-Eco <sup>®</sup> Modular		
Type of hood/housing	Hoods	
Description of hood/ housing	With integrated cable gland	

### Version

Locking type	Double locking lever
Size	10 B
Version	Side entry
Cable entry	1x M32

#### **Technical characteristics**

Limiting temperature	-40 +125 °C
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP65
Clamping range	13 21 mm

## Material properties

Material (hood/housing)	Polyamide Fibre-glass reinforced
Colour (hood/housing)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Page 1 / 2 | Creation date 2019-02-08 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## Specifications and approvals

Specifications	IEC 61984
	EN 45545-2 R22: HL1, HL2, HL3
	EN 45545-2 R23: HL1, HL2, HL3
	EN 45545-2 R24: HL1, HL2, HL3
UL / CSA	UL 1977 ECBT2.E235076
	CSA-C22.2 No. 182.3 ECBT8.E235076
Commercial data	
Packaging size	1
Net weight	150.8 g
Country of origin	Germany
European customs tariff number	85389099