

Han-Eco Mod.6 Outd.-HBM



| Part number | 19 41 206 0301 |
|--------------------|-------------------------------------|
| Specification | Han-Eco Mod.6 OutdHBM |
| HARTING eCatalogue | https://b2b.harting.com/19412060301 |

Identification

| Category | Hoods/Housings | |
|-------------------------------------------|---------------------------|--|
| Series of hoods/housings Han-Eco® Modular | | |
| Type of hood/housing | Bulkhead mounted housings | |

Version

| Locking type | Double locking lever |
|--------------|----------------------|
| Size | 6 B |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|----------------------------------------|-------------|
| Number of relockings | ≥500 |
| Degree of protection acc. to IEC 60529 | IP65 |

Material properties

| Material (hood/housing) | Polyamide Fibre-glass reinforced |
|------------------------------------------------------------|-------------------------------------|
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (seal) | FPM |
| Colour (seal) | RAL 7001 (silver-grey) |
| Material (locking) | Polyamide Fibre-glass reinforced |
| Colour (locking) | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0 |
| Material flammability class acc. to UL 94 (locking levers) | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |



Material properties

REACH SVHC substances No

Specifications and approvals

| Specifications | IEC 61984 EN 45545-2 R22: HL1, HL2, HL3 EN 45545-2 R23: HL1, HL2, HL3 EN 45545-2 R24: HL1, HL2, HL3 |
|----------------|--------------------------------------------------------------------------------------------------------------|
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |

Commercial data

| Packaging size | 1 |
|--------------------------------|----------|
| Net weight | 85.8 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |