

Datenblatt Art. 941.101

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

DESK2 RAIL Steckdoseneinheit

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung	2,0m H05VV-F 3G1,5mm²	Supply cable	2,0m H05VV-F 3G1,5mm²
Farbe Zuleitung	Schwarz	Colour supply cable	Black
Stecker	Wieland GST18i3	Plug	Wieland GST18i3
Stromausgang		Power output	
Steckdosen		Socket outlets	
2x CEE 7/3 (Type F)		2x CEE 7/3 (Type F)	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Mit erhöhtem Berührungsschutz		With shutter	
Schwarz, ähnlich RAL 9005, 35°		Black, similar to RAL 9005, 35°	
16A / 250V~, IP20		16A / 250V~, IP20	
Funktionsmodule		Function modules	
USB-Charger		USB charger	
Doppelcharger	3,1A 5V DC	Double charger	3,1A 5V DC
Weitere Produkteigenschaften		Further product attributes	
Plattform	Standard (kHE)	Plattform	Standard (kHE)
Material		Material	
Gehäuse:		Housing:	
Aluminium eloxiert		Aluminium anodised	
Abdeckung:		Cover:	
PA6 GF30 850°C, schwarz ähnlich RAL 9005		PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang		Scope of delivery	
1x DESKRAIL Steckdosenleiste		1x DESKRAIL power strip	
Im Karton		In carton	

Umgebungsbedingungen		Environmental conditions	
Maximale Höhe	0 - 3000m	Maximum height	0 - 3000m
Umgebungstemperatur bei Montage und Nutzung	5°C – 35°C	Surrounding temperature during mounting and use	5°C – 35°C
Vor direkter Sonneneinstrahlung schützen.		Protect from direct sunlight.	
Umgebungstemperatur bei Transport und Lagerung	-25°C - 60°C	Surrounding temperature during transport and storage	-25°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend)	5 – 95%	Relative humidity (non-condensing)	5 – 95%
Schutzart	IP20	Protection type	IP20
Konformität / Approbation		Conformity / Approval	
Bauart geprüft	DIN VDE 0620-1, DIN 49440	Type approved	DIN VDE 0620-1, DIN 49440

Zeichnung

Drawing

